

NW Marine Drive/Chancellor Boulevard/East Mall Intersection Redesign


Aaron Chen, Daniel Waine, Gerad van Agteren, Janet Jorgensen, Kanish Mathur, Pearl Ranchal

University of British Columbia

CIVL 446

April 08, 2016

Disclaimer: "UBC SEEDS Program provides students with the opportunity to share the findings of their studies, as well as their opinions, conclusions and recommendations with the UBC community. The reader should bear in mind that this is a student project/report and is not an official document of UBC. Furthermore readers should bear in mind that these reports may not reflect the current status of activities at UBC. We urge you to contact the research persons mentioned in a report or a SEEDS team representative about the current status of the subject matter of a project/report".



NW Marine Drive/Chancellor Boulevard/East Mall Intersection Redesign

Detailed Design Report

Client: UBC SEEDS Sustainability Program & UBC Campus and Community Planning

Proponent: Van Augustine Consultants (Team #5)

Aaron Chen
Daniel Waine
Gerad van Agteren
Janet Jorgensen
Kanish Mathur
Pearl Ranchal

April 8, 2016

Executive Summary

Van Augustine Consultants proposes the construction of a single lane roundabout at the intersection of NW Marine Drive, East Mall, and Chancellor Boulevard in order to provide a safer alternative to the current non-standard intersection layout. The single lane roundabout increases user safety by reducing vehicle speeds, reducing the number of conflict areas, and decreasing potential collision angles to angles less than 90 degrees. The new design also creates less driver confusion, and promotes sustainability by better accommodating pedestrians and cyclists. Stormwater management was a major criteria and was considered in depth during the design phase. This report builds on the Detailed Design Summary Report and Presentation delivered to UBC Campus and Community Planning February 29, 2016.

A major development since the preliminary design phase was the proposal of a bike parking facility, the Bike Garden. This showcase gateway feature realizes UBC's mission for sustainability and commitment to alternative modes of transportation. This facility provides storage for 84 bikes north of Allard Hall. The Bike Garden is a steel frame structure featuring a green roof and integration with the newly proposed stormwater management system. An Issued for Tender Structural and envelope drawing set is included in the report.

In a stormwater management context, cliff erosion along the northern edge of the campus has been a major concern for UBC. Therefore, minimizing infiltration and controlling surface runoff were key design parameters. Specifically, the detailed stormwater management design provides a reduction in the volume of runoff by lowering the impervious-to-pervious area ratio through the addition of rain gardens and pervious pavers, and better collection of surface run-off by adding six new catch basins. Furthermore, the additional captured stormwater will be diverted through a Stormceptor Oil and Grit separator and to an 800m³ underground stormwater detention facility allowing for attenuation and controlled release of stormwater to the minor system during high flow events. The project team has consulted with the Langley Concrete Group and Ibrium Systems for the sizing of the Stormceptor system to ensure water quality standards are sufficient to use captured stormwater for irrigation of the on-site landscaping, the bike garden green roof, and the Rose Garden. For the detailed design of the proposal, guidance was sought from the UBC 2015 Integrated Stormwater Management Plan and the Metro Vancouver 2012 Stormwater Source Control Guidelines.

The project (roundabout, Bike Garden, landscaping and drainage) is estimated to cost \$1.59 million for a September 2016 delivery. In terms of construction staging, Bike Garden construction begins May 1st, 2016, and roadwork begins June 3rd, 2016. This staging avoids potential conflicts between roadwork and the traffic surges associated with the annual UBC graduation ceremonies hosted at Chan Centre situated to the immediate southwest of the subject intersection. Furthermore, the majority of all roadwork will be performed with comprehensive traffic management and only periodic detours and partial closures. The redesigned intersection will be commissioned in time for September 1st.

Van Augustine Consultants will continue to involve stakeholders in the final stages of design. Crossing agreement requests will be sent to utility providers and a meeting will be setup with Metro Vancouver to mitigate any right-of-way conflicts. The project team will also seek input on the construction staging plan from the stakeholders including nearby residents, intersection users, and nearby event facility managers. Their input will be essential in ensuring that the construction of the new roundabout will be efficient and user friendly. The engagement plan involves a public open house, an online feedback forum, and the creation of the project website with information and updates regarding the project.

Table of Contents

1.0	Introduction	1
1.1	Project Objectives	1
1.2	Project Scope	1
1.3	Report Organization	2
1.4	Team Contributions To Detailed Design.....	3
2.0	Existing Conditions and Design Constraints	4
2.1	Transportation Infrastructure	5
2.2	Utilities	5
2.3	Key Design Constraints	6
3.0	Design Criteria	8
3.1	Design Criteria.....	8
3.2	Regulatory Considerations and Design Standards	9
4.0	Preliminary Design Recommendations	10
4.1	Traffic Forecasting.....	10
4.2	Intersection Options and Evaluation.....	11
4.3	Recommendations	12
5.0	Roadway Design.....	13
5.1	Geometric Design	14
5.2	Survey Layout and Site Profile	15
5.3	Pedestrian and Cycling Connectivity.....	15
5.4	Pavement Design	16
5.5	Utility Coordination	18
6.0	Integrated Stormwater Management Strategy	19
6.1	Existing Conditions	19
6.2	Technical Guidelines and Site Specific Targets	21
6.3	Absorbent Landscaping and Pervious Surface Cover	22
6.4	Catchbasin Relocations.....	24
6.5	On-site Stormwater Treatment and Detention	25
7.0	Gateway Feature.....	27
7.1	Integration With UBC Planning Objectives	27
7.2	Structural Design.....	28
7.3	Architectural, Landscape and Sustainability Considerations.....	30
8.0	Construction Planning.....	32
8.1	Construction Schedule	32
8.2	Construction Staging Plan.....	33
8.3	Pre-Tender Cost Estimate	34
8.4	Risk Assessment.....	36
8.5	Stakeholder Engagement	38
9.0	Closing	40
	References.....	42

APPENDICES

Appendix A	IFT Drawing Set
Appendix B	Site Photos
Appendix C	Conceptual Design Options
Appendix D	Stormwater Design
Appendix E	Structural Design
Appendix F	Construction Schedule
Appendix G	Pre-Tender Cost Estimate
Appendix H	Permit Application Forms
Appendix I	Risk Assessment
Appendix J	Stakeholder Engagement

LIST OF FIGURES

Figure 1: Land Ownership near Project Intersection	4
Figure 2: Aerial View of Exiting Intersection	4
Figure 3: Exiting Utilities	6
Figure 4: Key Site Constraints and Design Considerations	7
Figure 5: Daily Person Trips to UBC 1997-2012	10
Figure 6: Proposed Intersection Layout	13
Figure 7: Cyclist Ramp Detail.....	16
Figure 8: Typical Pavement Section	17
Figure 9: UBC Storm Sewer Catchments	19
Figure 10: Point Grey Subsurface Conditions.....	20
Figure 11: Ponding Along North Curb Alignment.....	20
Figure 12: Typical Rain Garden Detail	23
Figure 13: Permeable Truck Apron Detail.....	24
Figure 14: Type C Catchbasin Capture Curves	25
Figure 15: Double Trap StormTrap System.....	26
Figure 16: Stormceptor Oil and Grit Separator System	26
Figure 17: Bike Garden and Surroundings	27
Figure 18: Roof Framing Plan	29
Figure 19: West Elevation	29
Figure 20: Bike Garden North West View.....	30
Figure 21: Cedar Siding Detail	31
Figure 22: Construction Phasing.....	33
Figure 23: Possible Property Encroachment Area	37
Figure 24: Stakeholder Engagement Plan	39

LIST OF TABLES

Table 1: Project Team Contributions to Detailed Design	3
Table 2: Design Criteria	8
Table 3: Projected Change in Intersection Volumes 2014 - 2030	10
Table 4: Multi-Criteria Decision Matrix Results.....	11
Table 5: Geometric Design Summary	14
Table 6: Pavement Material Specifications	17
Table 7: Federal and Provincial Stormwater Design Guidelines and Targets.....	21
Table 8: Pre vs Post Development Flow Rates.....	22
Table 9: Summary of Design Loading	28
Table 10: Green Roof Planting Schedule	31
Table 11: Key Project Milestones	33
Table 12: Pre-Tender Cost Estimate	34
Table 13: Key Project Risks	36

List of Abbreviations

BC	British Columbia
BCBC	British Columbia Building Code
CCC	Construction Completion Certificate
CSA	Canadian Standards Association
ESAL	Equivalent Single Axial Loading
FHWA	Federal Highway Association (for the United States)
IFC	Issued For Construction
IFT	Issue for Tender
ISMP	Integrated Stormwater Management Plan
MoTI	Ministry of Transportation and Infrastructure (for the Province of British Columbia)
MSU	Medium Single Unit Truck (refer to TAC Geometric Design Manual)
NBCC	National Building Code of Canada
NW	Northwest
RAP	Reclaimed Asphalt Pavement
TAC	Transportation Association of Canada
WB-19	Semitrailer Classification (refer to TAC Geometric Design Manual)
WB-21	Semitrailer Classification (refer to TAC Geometric Design Manual)
UBC	University of British Columbia

1.0 Introduction

Van Augustine Consultants has been retained by UBC Campus and Community Planning to redesign the NW Marine Drive, Chancellor Blvd. and East Mall Intersection. This report summarizes the detailed design of the intersection with the intent to provide details for UBC Campus and Community Planning and other stakeholders.

1.1 Project Objectives

Located at the north end of campus, the intersection sits at the confluence of UBC Campus, the University Endowment Lands and Pacific Spirit Park and serves as one of the five gateways to UBC's Point Grey Campus. The primary objective of this redesign project is to propose a safer and more efficient alternative to the current layout of the intersection. This redesign aims to better accommodate all elements of the traffic spectrum including heavy vehicles, bikes and pedestrians while aligning the intersection space with UBC's sustainability and transportation goals.

1.2 Project Scope

As mentioned earlier, the current non-standard configuration of the intersection results in inefficient and unsafe operation during peak periods. This detailed design report builds on the results and feedback from the NW Marine Drive / Chancellor Boulevard / East Mall Intersection Redesign Detailed Design Summary Report from February 2016, and covers the scope of work outlined below:

- Gather, review and forecast existing site and traffic data.
- Model existing site and traffic conditions to test prospective intersection configurations, control types, and orientations.
- Select and develop the best-suited intersection design using the client-submitted design criteria.
- Develop a detailed design roadway concept that offers operational improvements to the existing intersection and features the intersection as a gateway to UBC's Point Grey Campus.
- Deliver the Bike Garden's structural design complete with the green roof, and in accordance with CSA A23.3-14 and CSA S16-14.
- Prepare a stakeholder engagement and communication plan.
- Prepare detailed cost and construction schedules with a construction start date of May 1, 2016.
- Prepare a set of issued-for-tender design drawings complete with sections, plans, elevations, and details for the roadwork, the associated pavement structure, and the Bike Garden.

1.3 Report Organization

The layout of this report follows the key stages in the design process. It begins with a clear outline of the existing site conditions and identifies key considerations addressed in the design process. The next section outlines design criteria and lists the design standards reinvent to the intersection design. Section 4 summarized work completed in the conceptual and preliminary design phases and the recommendations put fourth in the Preliminary Design Report.

Section 5, highlights key elements of the roadway design that were refined during th detailed design process. A key feature of the proposed roundabout is an integrated stormwater management system outlined in Section 6. The stormwater system ties the roadway and the gateway feature together into the underground stormwater storage tank. The gateway feature, the Bike Garden, is described in Section 7, which includes details on architecture considerations and structural design.

Section eight covers the construction planning efforts that assure the project is ready for a May 1, 2016 Start Date. Included in this section is a detailed construction schedule, construction phasing plan, pre-tender cost estimate, risk assessment and stakeholder engagement strategy. The report's final section provides a summary of the key project elements and outlines final revision process that will lead to the issue of the project tender.

A set of construction drawing have been prepared for review prior to the issue of tender April 11, 2016. A list of drawings is included below; the full drawing package can be found in Appendix A. Additional design detailed and supporting information in provided in Appendix B through J.

Issue for Tender Drawing Set (Refer to Appendix A)

A0	Plan Rendering	S0	UBC Bike Garden 3D View
A1	Traffic and Signing	S1	UBC Bike Garden Ground Floor
A2	Geometric Design	S2	UBC Bike Garden Roof Framing
A3.1	Existing Storm System	S3	UBC Bike Garden West Elevation
A3.2	Proposed Storm Water Management Plan	D1	Roof Assembly 1
A4	IP Ratio	D2	Roof Assembly 2
A5	Phase 3: Removals and Detour Road Construction	D3	Wall Assembly 1
A6	Phase 4: South Chancellor BLVD Construction	D4	Asphalt Assemblies
A7	Phase 5: East Mall Construction	D5	Rain Garden Details
A8	Phase 6: NE Marine Drive Construction		
A9	Phase 7 Roundabout Construction		
A10	Phase8: North Chancellor BLVD and East Mall Construction		
A11	Roadway Sections		

1.4 Team Contributions To Detailed Design

The following table summarizes the contributions of each team member to development of the detailed design and the compilation of this report. Contributions are organized by report sections and identify primary and secondary contributors as well and reviewer roles.. Separate categories have been included for drafting as a considerable amount of time and effort was dedicated to this task.

Table 1: Project Team Contributions to Detailed Design

Report Component	Primary Contributor	Secondary Contributor	Reviewer
Executive Summary	DW	PR	JJ
1.0 Introduction	KM	GVA	DW
2.0 Existing Conditions	PR	JJ	GVA
3.0 Design Criteria	GVA	JJ	PR
4.0 Preliminary Design Recommendations	KM	DW	JJ
5.0 Roadway Design	GVA	JJ	PR
6.0 Stormwater Design	JJ	AC	GVA
7.0 Gateway Feature	DW	KM	GVA
8.0 Construction Planning	PR	GVA	JJ
9.0 Closing	JJ	PR	KM
Design / Project Element	Primary Contributor	Secondary Contributor	Reviewer
Roadway Design – Geometric Layout	GVA	DW	KM
Roadway Design – Pavement Structure	GVA	DW	KM
Pedestrian/Cycling Facilities + Signage	GVA	JJ	PR
Stormwater Design – Overland Flow	JJ	PR	GVA
Stormwater Design – Minor System Upgrades	JJ	AC	GVA
Stormwater Design – Rain Gardens	JJ	PR	GVA
Bike Garden – Structural Design	KM/DW	GVA	PR
Bike Garden – Envelope + Green Roof	GVA	KM/DW	JJ
Roadway Design Drawings & Drafting	GVA	JJ	DW
Gateway Feature Drawings & Rendering	KM/DW	GVA	PR
Quantities and Cost Estimate	PR	KM	JJ
Construction Schedule & Staging	JJ	GVA	DW
Stakeholder Engagement Strategy	JJ	DW	KM
Risk Assessment	PR	KM	DW
Report Compilation	PR	KM	All

2.0 Existing Conditions and Design Constraints

Located at the north end of campus, the intersection sits at the confluence of UBC Campus, the University Endowment Lands and Pacific Spirit Park as shown in Figure 1. Figure 2 identifies adjacent landowners and facilities including the Chan Centre of Performing Arts, Allard Hall Law School, Chancellor Place University Neighborhood and University Endowment Lands and Metro Vancouver as the owner of Pacific Spirit Park. The intersection itself is maintained and operated by BC Ministry of Transportation Infrastructure (MoTI). This section provides an overview of the site features relevant to the intersection redesign.



Figure 1: Land Ownership near Project Intersection
(UBC, 2012)



Figure 2: Aerial View of Existing Intersection
(Image Source: Google Maps)

2.1 Transportation Infrastructure

The intersection in question is at the north end of campus, at the end of East Mall. Chancellor Boulevard begins at the intersection and heads east, NW Marine approaches from the west and turns north. The east-west roads have right of way, and the north-south roads are controlled by stop signs. The intersection slopes down south to north, and is relatively flat east to west. Key aspects of the roadway network are described below:

- **Roadway Classification:** the through route on NW Marine Dr. and Chancellor Blvd. as a community shuttle route; the western leg of NW Marine Dr. as a collector road; and both the northern leg of NW Marine Dr. and Chancellor Blvd. as arterial roads with bike traffic (UBC, 2014).
- **Cycling Facilities:** Bike lanes are clearly marked for bike traffic in all direction for roads east, west, and south of the subject intersection. However, no separate bike lane is provided along either direction of the northern leg of NW Marine Dr.
- **Pedestrian Facilities:** A pedestrian crosswalk across Chancellor Blvd. is situated to the immediate east of the intersection. For the western leg of Marine Dr, and East Mall, pedestrian crosswalks are moved 60m and 80m away from the intersection, respectively. No crosswalk is present across the northern part of NW Marine Dr.
- **Transit:** Two transit stops, one for either direction, are present west of the intersection along NW Marine Dr. These two stops are the only transit access stops present within a 400m radius of the intersection and are part of Tranlink's community shuttle route.
- **Emergency Vehicle Access:** An emergency vehicle access point is along westbound NW Marine drive on the West side of the intersection.

2.2 Utilities

The high density of utilities present at the intersection is an important design consideration. Figure 3 below provides a schematic of the existing utilities present at the intersection. The deep and shallow utilities present within the project boundary are summarized below.




Figure 3: Exiting Utilities
(Image Source: Krista Falkner, 2015)

- **Deep Utilities:** Several sanitary lines converge at the center of the intersection. A storm main zigzags across the intersection connecting a series of manholes and several small feeder lines. Each of these two utilities are connected through a large number of manholes across the project site. Two water mains are present to on the west side of the project site but are unlikely to impact the project.
- **Shallow Utilities:** There are several streetlights of varying decorative standards lining the streets on the three sides of the intersection while the northern alignment of NW Marine Drive does not have street lighting. Two gas lines, one along either shoulder, are embedded along Cecil Green Park Rd. to the south west of the intersection. These lines are fed by a line buried along the western shoulder of Iona Drive. Two power and electrical ducts are installed south of the East Mall pedestrian crosswalk. Additionally, a small portion of the sidewalk along the northern shoulder of NW Marine Dr.'s western alignment.

2.3 Key Design Constraints

The existing, non-standard intersection configuration and surrounding project area presents a number of issues and constraints that have been addressed through the design process. Key site constraints and

design considerations are summarized below and identified in Figure 4. Specific site details documented through site visits are included in Appendix B for further reference.

- Shifts in horizontal alignment across the intersection and skewed approaches on the north and south sides of the intersection,
- Insufficient connectivity of pedestrian facilities,
- Excessive signage and an unconventional centre median that are inconsistent with user expectation,
- Surface drainage and ponding on the north curb alignment observed during site visits,
- Bus stops and emergency vehicle access points that need to be accommodated throughout construction.
- A larger number of landowners and university facilities and stakeholders to engage throughout design and construction processes.



Figure 4: Key Site Constraints and Design Considerations

3.0 Design Criteria

Throughout the conceptual, preliminary and detailed design phases; the project team has worked to address these key site concerns by evaluating all design decisions using a comprehensive set of design criteria. This section includes a brief overview of each design criteria category as well summary design guidelines and regulatory considerations relevant to the project.

3.1 Design Criteria

Using objectives outlined in the RFP, as well as the goals and targets outlined in the 2014 Transportation Plan, UBC Campus Plan, and UBC Land Use Plan, the project team has established a comprehensive set of design criteria. These criteria have been organized into three broad categories: safety, operational efficiency and sustainability as shown below in Table 2. A comprehensive list of design criteria can be found in the Preliminary Design Report.

Table 2: Design Criteria

Safety	Operational Efficiency	Sustainability: Tipple Bottom Line
<ul style="list-style-type: none">Collision points and severityIntersection sight distanceSignageLightingEmergency Access	<ul style="list-style-type: none">Synchro Outputs: v/c ratio, LOS, Delay and Queue LengthAccommodation of event volumesAccommodation of cyclists, pedestrians and transit	<ul style="list-style-type: none"><u>Social</u>: Gateway Feature, Traffic Noise, protection of pedestrian core, constructability<u>Economic</u>: Capital costs, life cycle cost, risk/uncertainty<u>Environmental</u>: change in impervious area, stormwater management, and alignment with UBC planning objectives.

Typically, Van Augustine Consultants would recommend that the design criteria be developed in consultation with UBC Campus and Community Planning and targeted stakeholder groups. However, schedule constraints and project limitations did not permit such engagement at the design development stage. As extensive stakeholder engagement was completed as part of the 2014 UBC Transpiration Plan and the construction of the 16th Avenue Westbrook Mall roundabout. Stakeholder reports from the 16th Avenue Roundabout construction and targets and goals outlined in UBC planning documents were assumed to represent stakeholder interests and used to inform the priority weighting in the evaluation of the intersection.

3.2 Regulatory Considerations and Design Standards

UBC Planning Documents including the UBC 20-Year Sustainability Strategy (2015), UBC Campus Plan (2012) and the UBC Transportation Plan (2014) have been foundational to the design development process. Key documents that have been used to establish technical design criteria and minimum design standards for specific design elements are included below:

Roadway Design

- Transportation Association of Canada (TAC) Geometric Design Guidelines (1999)
- BC Ministry of Transportation Supplement to TAC Geometric Design Guidelines (2007)
- Kansas Roundabout Design Manual (2014)
- MoTI Manual of Standard Traffic Signs and Pavement Markings (2000)
- MoTI Pavement Structure Design Guidelines (2015)
- As requested by UBC, all intersection movements were designed to accommodate a WB-17 design vehicle with through movements along Chancellor Blvd and NW Marine Drive able to accommodate a WB-20 design vehicle.

Stormwater Design

- DFO Canada Urban Stormwater Management Guidelines and Best Practices, (2001)
- BC Stormwater Management Guidebook (2002)
- Metro Vancouver Stormwater Source Control Guideline (2012)
- UBC Integrated Stormwater Management Plan (2015)

Structural Design

- National Building Code of Canada (2010)
- British Columbia Building Code (2012)
- CSA A 23.3-14 Design of Concrete Structures (2014)
- CSA S16-09 Steel Design Handbook – 10th Edition (2009)
- CSA S136-12 North American Specification for the Design of Cold-Formed Steel Structural Members

As a retrofit project where design standards for new construction could not be met, emphasis was placed on demonstrating an improvement in safety and performance over the existing condition.

4.0 Preliminary Design Recommendations

During the conceptual design phase, the Project Team considered three intersection options. These designs were evaluated against the design criteria and a single lane roundabout was selected as a preferred option. The preliminary design phase largely focused on developing the geometric configuration of the roundabout to optimize the operational efficiency and safety design criteria. This section summarizes the options considered, key aspects of the early design development and justification for the proposed design. A detailed account of the preliminary design decisions can be found in the Preliminary Design Report submitted to the UBC SEEDs Sustainability Program on December 4, 2015.

4.1 Traffic Forecasting

Design traffic volumes for the 2030 horizon were generated by augmenting the client-supplied traffic counts with the campus growth projections identified in the UBC 2014 Transportation Plan and data from UBC Transportation Status Reports. A summary historical transportation trends to and from UBC Campus and the forecasted percent change in intersection volumes at the project intersection between 2014 and 2030 is provided in Figure 5 and Table 3 respectively.




Figure 5 Daily Person Trips to UBC 1997-2012
(UBC, 2014)

Table 3: Projected Change in Intersection Volumes
2014 - 2030

Mode Choice	Percent Change 2014 - 2030
SOV	-14%
Heavy Vehicles	38%
Bikes	-37%
Pedestrians	-27%

As the subject intersection provides thoroughfare for the Chan Centre and the Museum of Anthropology (MOA), additional trips were generated and distributed around the intersection to account for attendance at events held at both facilities. This produced an additional 473 passenger moving through the intersection in the east-west direction and an additional 53 passenger cars accessing the event facilities via the North Leg of NW Marine Drive. Event volumes both arriving and leaving the campus were modeled in conjunction with p.m. peak hour traffic to ensure the proposed intersection configurations are able to accommodate higher than normal traffic volumes both during and outside of peak hour traffic.

4.2 Intersection Options and Evaluation

Three intersection concepts were developed to address the safety and operational efficiency issues at the intersection. As required by BC Ministry of Transportation, a roundabout was considered as a first option. Two convention intersection configurations were also developed. Each conventional layout offered options for either signal or two-way stop controls with restrictions to intersections movements where required to ensure safety. Figures of each conceptual design option are included in Appendix C.

The a.m. and p.m. peak hour operating conditions at the intersection were modeled using the Synchro software package based on the methodology outlined in the Transportation Research Board Highway Capacity Manual. The existing intersection configuration and each proposed configuration was assessed based on the level of operating service (LOS), volume to capacity ratio (v/c), average vehicle delay and 95th percentile queue length. These assessments were performed for current traffic volumes, design volumes at the 2030 horizon year, and also under event volume spikes. Detailed outputs from the traffic analysis can be found in the Preliminary Design Report.

In order to numerically and objectively evaluate the design options a Multi-Criteria Decision Matrix (MCDM) was implemented. This process allows for an objective and logical approach to the determination of a recommendation. The design criteria were evaluated by weighing and normalizing the assigned scores for each criterion. Evaluation results were normalized at two levels, within each design criteria category, and again between categories based on both the priority assigned to each individual criterion and to the criteria categories. Table 4 summarizes the evaluation results based the overall design criteria categories. A more detailed explanation the design evaluation can be found in the Preliminary Design Report.

Table 4: Multi-Criteria Decision Matrix Results

Criteria Category	Priority	Option 1	Option 2	Option 3
Safety	5.00	8.9	6.6	7.7
Operational Efficiency	3.50	9.1	6.7	7.7
Sustainability	1.50	7.3	8.5	7.4
Total	10	8.7	6.9	7.7

4.3 Recommendations

Based on the results of the MCDM, a single lane roundabout (option 1) configuration was recommended. The key design features of the proposed preliminary design are summarized below:

Safety benefits include:

- Forced reduction in speed upon approach giving drivers more time to react and avoid potential conflicts with other vehicles, bikers, and pedestrians.
- A reduction in the number of potential conflict points between vehicles, bikes, and pedestrians and the elimination of more severe head-on and T-bone types of collisions.
- Shorter crossing distances and reduce crossing delays which intern reduces the number of illegal pedestrian crossings.

Operational efficiency benefits include:

- Reduced traffic delays and queue lengths. Traffic models indicate that a single lane roundabout provides equivalent or improved LOS under peak hour and event traffic demands.
- Increased capacity. The roundabout significantly outperformed the conventional intersection options under higher event volumes in the Syncro traffic models

Sustainability features include:

- Increased in total pervious area due to narrower lanes and opportunities to use permeable paving stones at the truck apron.
- Reduced noise and emissions due to lever speeds, less idling and less instances where vehicles will be required to accelerate from a stopped position.
- The added pervious area around the roundabout creates opportunities to use landscaping features for a natural systems approach to stormwater management.

The key detailed design features summarized in the remaining sections of this report build on the design features identified above. They focus on optimizing the intersection layout with emphasis on promoting safety, efficiently and sustainability while advancing the design elements to the tender ready stage.

5.0 Roadway Design

Building on the geometric initial layout established in the preliminary design phase, elements of the overall roadway layout have been finalized to a tender ready stage. Conformance to UBC's goals regarding the corridor has been maintained and the final curb and asphalt layout details have been measured against all criteria developed in earlier design stages. This criterion includes the fundamental elements discussed in the preliminary design: optimization of safety, operational efficiency and sustainability features of the intersection. The categories critical to the road design are described in the following section and include the roundabout geometry, pedestrian and cyclist connectivity, roadway material selection, grading requirements for the roadway profile and utility coordination. A high level image of the new layout, updated from the preliminary design, has been included below in Figure 6.




Figure 6: Proposed Intersection Layout

5.1 Geometric Design

During the detailed design, curb and lane positions were finalized based on the parameters defined in the preliminary design. These parameters not only maximize the capacity and the safety of the proposed design, but also implement the ideal geometric layout. The proposed geometric configuration encourages drivers to enter and circulate the roundabout at controlled speeds. Such controlled traffic movement maintains a desirable level of safety around the intersection without compromising its operational efficiency.

Like the safety requirements, the operational efficiency requirements determined in the earlier design stages have also been maintained in the final layout. This is a critical aspect of the design because while the reduced speeds boost safety, they also have the potential to compromise the efficiency of traffic flow. Thus, to maintain unobstructed flow, optimum parameters for roundabout size and position, ideal vehicle turn path and fastest path were computed in the preliminary design and have now been implemented in detail as outlined in the final geometric layout. Further to this, the final version of the curb layout, proposed as part of the detailed design, has been reviewed for compliance with the three criteria noted above. The final design parameters are summarized in the table below.

Table 5: Geometric Design Summary

Design Parameter	Roundabout Element	Dimension
Size and Position Optimization	Inscribed Circle Diameter	37 m
Turn Path Analysis	Truck Apron Diameter	26 m
	Raised Central Island Diameter	6.4 m
	Circulatory Lane Width	4.6 m
Fastest Path Analysis	Approach Lane Width	3.7 m
	Entry Deflection Radii	30m – 60m
	Exit Deflection Radii	60m – 90m
	Approach Speed	50 km/hr
	Circulatory Speed	30 km/h
Curb and Gutter	Inner Roundabout Curb	200mm Standard C&G
	Truck Apron Curb	Roll Face C&G
	Approach and Median Curbs	200mm Standard C&G
Pedestrian & Cycling Facilities	Bike Lane Width	1.5 m
	Sidewalk/Pathway Width	2.0 m
	Crosswalks	3.0 m

5.2 Survey Layout and Site Profile

Survey points indicating the exact positions of the curbs at each critical road curve location are shown on Drawing A2 in Appendix A. Worth noting is that the survey points reference the original datum of the site determined from the original CAD layout and will be used for construction layout survey. The contractor will be required to complete a detailed site survey prior to the commencement of the roadway construction to confirm the proposed pavement tie-in points and final grade elevations. Cross-sections of both east-west and north-south directions of the roundabout are provided in Drawing A11 Appendix A. The pre-construction site survey noted above will also confirm the vertical alignment of the proposed cross-sections. In addition, the topographical information from the said survey will help confirm that the proposed design does not alter the existing drainage pattern undesirably.

5.3 Pedestrian and Cycling Connectivity

An emphasis on pedestrians and cyclists in the development of the overall intersection design has been maintained throughout the preliminary and detailed design phases. This objective was addressed in the geometric design by reducing the speed of vehicles circulating the roundabout, creating a safer crossing environment for both pedestrians and cyclists. Additional features that promote pedestrian and cycling connectivity and safety are shown on Drawing A1 in Appendix A and are summarized below:

- **Pedestrian Treatments:** Pedestrian crossings have been accommodated on all sides of the intersection, oriented perpendicular to the lanes to minimize crossing distances. The final layouts of the crosswalks include ramps indicated at all required locations to accommodate wheelchairs. The final positions of the crosswalks were determined based on an optimized layout to reduce travel time and the potential for jaywalking.
- **Acoustic Pedestrian Crossing Signals:** Finding sufficient gaps in traffic to enable safe crossing is a particularly difficult task for visually impaired users. Due to high peak hour east-west traffic volumes, acoustic pedestrian crossing signals are proposed along all north-south pedestrian crossings.
- **Bike Treatments:** As not all cyclists will be comfortable merging into existing traffic and navigating the roundabout in the circulatory lane, bicycle ramps have been provided at each approach leg. The dedicated bike lanes terminate at the ramps, and the cyclist is given the option of merging into the regular traffic stream or exit in the roadway via the ramp. The ramp

configuration, shown in Figure 7 below, is constant with those proposed by Bunt & Associates (2016) in the design of the Chancellor Blvd and Westbrook Mall roundabout.




Figure 7: Cyclist Ramp Detail

5.4 Pavement Design

Pavement types are specified based on road classification and the anticipated traffic loading over a 20-year design life. Traffic loading is measured in equivalent single axial loads (ESALs). While the volumes through the intersection are relatively low, since Chancellor Blvd and NW Marine Drive are designated truck routes, the pavement design has been based of MoTI Type A Pavement (2015). A summary of the proposed pavement structure based on MoTI Guidelines is provided in Table 6. The proposed design includes MoTI's new provisions for the use of reclaimed asphalt pavement (RAP) material in hot mix asphalt construction. The pavement design will need to be confirmed by geotechnical sub-consultant through asphalt cores to ensure structural performance and tie in to the existing structure.




Figure 8: Typical Pavement Section

Table 6: Pavement Material Specifications

Structural Element	Material	Thickness
Top Lift Asphalt	Hot Mix Asphalt with PG 58-28 Binder 30% RAP Content	50mm
Base Lift Asphalt	Hot Mix Asphalt with PG 58-28 Binder 30% RAP Content	100mm
Crushed Base Course	25mm Open Graded Base	300mm
Separation Fabric	Geotextile Fabric Material	-
Select Granular Sub-Base	75mm Crushed Gravel	300mm

The final design of the roundabout truck apron consists of a mountable curb installed at its perimeter as well as visually distinct paving stones so large trucks can navigate turns. Drainage at this location will be facilitated through the use of permeable pavers and a perforated perimeter drainage pipe directed towards the storm drainage system. See Drawing D4 for a detailed layout of truck apron materials including sub-base, geotextile overlays, and aggregate bedding layers.

Colored paving stones, in place of a standard asphalt or concrete road surface, are proposed for the truck apron to provide a visually distinct surface. This will discourage drivers in standard sized vehicles from using the truck apron. The stone color will also be distinctly different from the concrete sidewalks to discourage pedestrians from crossing into the interior of the roundabout.

5.5 Utility Coordination

Utility coordination will be a critical element to address early on in the construction process. The utility schematic released by UBC Campus and Community Planning revealed that the intersection hosts a significantly dense network of both deep and shallow utilities comprised of storm, sewer, water, electrical, and fiber cable services. No information, however, is available for the depths and offsets associated with any utility. Thus, the contractor is required to seek utility depths and offsets through crossing agreements with individual utility providers.

Aside from catchbasin relocations, all other existing deep utility infrastructure will be largely unaffected by the proposed intersection upgrades. Manhole rims and valve stems, however, will need to be adjusted to match the final grade profile. Locations of manholes and valves have been estimated based on site visits and utility schematics provided by UBC Campus and Community Planning. The contractor must verify these locations prior to construction. Given the uncertainty in the depths and offsets associated with the existing storm and sewer mains under the intersection, assumptions had to be made in the course of the detailed design of the proposed integrated stormwater management system. Some of the key assumptions governing the risks associated with the proposed design are as follows:

- It is assumed that the sanitary main is significantly deeper than the storm main running underneath the intersection. This is a reasonable assumption on the part of the proposed design because it generally holds true in most existing utility corridors in the Metro Vancouver area. However, the expectation that the utility layout underneath the subject intersection conforms to standard practice does not mitigate the risk associated with this assumption. Therefore, the contractor must obtain the alignments and depths of the storm and sewer utilities from the relevant utility owners, and verify the depths and locations using ground-penetrating radar prior to commencing roadwork.
- At the time of the detailed design the condition of the existing catchbasins and manholes was estimated through visual inspections. Based on the results of such inspections, the need for replacing or salvaging the catchbasins and manholes was determined. In assuming a particular piece of infrastructure to be worth salvaging, it was assumed that its associated pipework was also worth salvaging. Such assumptions may be confirmed or refuted only on the basis of inspections performed through excavation.

6.0 Integrated Stormwater Management Strategy

The proposed stormwater strategy is inspired by the UBC 20-Year Sustainability Strategy and Board of Governors Policy #39 which encourage a natural systems approach to managing stormwater on campus (UBC 2014b). The design achieves provincial and federal volume control, rate control and water quality objectives through a integrated system of absorbent landscaping features, minor system upgrades and the installation of a Stormceptor oil and grit separator and underground stormwater detention facility. Furthermore, the Stormceptor and modular underground detention system allows for on-site stormwater re-use and is pre-qualified for LEED credits under the Sustainable Site, Water Efficiency and Material and Resources categories (Stormceptor, 2015, StormTrap, 2011b). Stormwater Drawings are included in Appendix A (Drawings A3.1, A3.2 and A4) and additional design details are provided in Appendix D.

6.1 Existing Conditions

The recently released UBC Integrated Stormwater Management Plan recognizes distinct challenges for the Point Grey Campus. The NW Marine Dr/Chancellor Blvd/East Mall intersection is situated within the north campus catchment shown in red in Figure 9 below. The minor storm system in the north catchment area is channeled through the Spiral Drain to an outfall at the lower cliff face. Surface runoff in proximity to the intersection generally flows north toward NW Marine Drive and Pacific Spirit Park.




Figure 9: UBC Storm Sewer Catchments
(UBC Energy and Water Services, 2016)

This of campus is particularly vulnerable to cliff erosion through both overland and infiltrated flows. Subsurface conditions along the Point Grey peninsula consist of approximately 0.5m of topsoil, underlain by up to 30m of glacial till followed by a Quadra Sand unit. This Qaudra sand unit creates upper and lower aquifers that are separated by the impermeable layer of silt. The aquifers are tilted towards the north and west resulting in sub-surface water that flows the cliff face in Pacific Spirit Park casing subsurface seepage erosion (Russel, 2005). This phenomenon is shown in Figure 10.




Figure 10: Point Grey Subsurface Conditions
(Russel, 2005)



Figure 11: Ponding Along North Curb Alignment
(Documented September 21, 2015)

In addition to subsurface drainage concerns, there are a number of surface drainage issues that need to be addressed. The localized ponding due to poor surface grading shown in Figure 11 was noted on a site visit on September 21, 2015. The UBC Overland Flow Study completed by Urban Systems in 2012, identified the project intersection as prone to approximately 680 m³ will flood the intersection in a 1:100 year storm event (Bell, 2012). This area is of particular concern as there currently no way to stop overland flows from entering Pacific Spirit Park and travelling down Marine drive where it spills over the cliffs and onto the Spanish Bank Beaches.

An extensive stormwater assessment of the project area completed as a part of the UBC ISMP. Study results indicate that minor system undersized for current demand leading to heightened flooding risks in storms larger than a 1:10 year event. The ISMP recommends that a stormwater detention facility be built

in this location to detain excess stormwater in high flow events. The facility would attenuate its release of stormwater into the storm system to lessen the demand on the Spiral Drain during high flow events.

6.2 Technical Guidelines and Site Specific Targets

Urban stormwater runoff is regulated at the federal, provincial and municipal levels. The Department of Fisheries and Oceans (DFO) and the BC Ministry of Water, Land and Air Protection outline specific guidelines and targets regarding the reduction of runoff volume and rates, the conveyance of peak flows during high flow events and water quality. These guidelines are summarized below in Table 7.

Table 7: Federal and Provincial Stormwater Design Guidelines and Targets

Level	Federal Guidelines & Targets	Provincial Guidelines & Targets
Reference Document	<i>DFO Urban Stormwater Management Guidelines and Best Practices, 2001</i>	<i>BC Stormwater Management Guidebook, 2002</i>
Volume Reduction	Retain the 6-month/24-hour post-development volume from impervious areas on-site and infiltrate to ground.	Capture 0 to 50% of the MAR at the source (building lots and streets) and infiltrate, evaporate, or reuse it.
Runoff Rate Control	Reduce post-development flows to pre-development levels for the 6-mth/24-hr, 2-yr/24-hr, and 5 yr/24-hr precipitation events.	Store 50% to 100% of MAR runoff and release at a rate that approximates the natural forested condition.
Peak Flow Conveyance	None	Ensure that the drainage system is able to convey extreme storm events (up to 100-yr. return period) with only minimal damage to property.
Water Quality	Collect and treat the volume of the 24-hour precipitation event equaling 90% of the total rainfall from impervious areas with suitable BMPs.	Refer to DFO Requirements
Notes:	MAR = Mean Annual Rainfall, 1:2.33 year storm event (1:2 year storm event used for design)	

At the local level, the Metro Vancouver Stormwater Source Control Guideline (2012) and the UBC Integrated Stormwater Management Plan (2015) defer to the targets set out by DFO and BC Ministry of Water, Land and Air Protection and promote the use of low impact stormwater features such as absorptive landscaping and stormwater reuse. Furthermore, UBC's 20-year sustainability strategy UBC Board of Governors Policy #39 places a strong emphasis on a natural systems approach to Stormwater management on campus.

In lieu for detailed topographic information for all upstream and downstream catchment areas, the proposed strategy aims to demonstrate an improvement relative to the exiting site conditions and accommodate future upstream and downstream improvements. Overall the objective of the design is to demonstrate a "Positive Net Impact" post-development scenario through the following design targets:

- **Volume Reduction and Peak Flow Conveyance:** short term onsite storage is can accommodate 100% of the MAR and 100% of the 1:100 year runoff volume,
- **Runoff Rate Reduction:** there is a reduction in peak flow rates in the major system with no notable increase in minor system,
- **Water Quality:** a minimum of 85% of TSS is removed from 100% of the 100-yr, 24-hr runoff volume.

To assist in stormwater design and evaluation site scale stormwater runoff model has been generated using XPSWMM and a water quality model was creating using PCSWMM. The models utilize a Horton infiltration model and the native glacial till soil has been assumed to have similar hydraulic conductivity to silty clay type soil to simulate the low permeability indicated by Russel (2005). Model results and design details can be found in Appendix D.

6.3 Absorbent Landscaping and Pervious Surface Cover

The narrow lanes that reduce traffic speeds and improve intersection safety also reduce overall asphalt surface area and allow the addition of more landscaped pervious surface cover. In total the propped intersection adds an additional 910 m² of pervious surface cover to the intersection through a combination of landscaped medians and islands, permeable paving stones at the truck apron and the elimination of the pavement on the lower stretch of Iona Dr. Drawing A4 in Appendix A shows the change in pervious and impervious surface cover between pre and post development conditions.

This increase in permeable surface cover reduces runoff rates in the post-development condition. Table 8 provides a comparison of the pre-and post development flow rates under the 5min and 24 hour 1:2 year (MAR) and 1:100 year design storms. Overall the reduction in I/P ratio from 1.19 to 0.90 creates a 8% reduction in post development flow rates when compared to pre-development flows. The flow rates have been established using rational method analysis and localized catchment areas. Results should be confirmed with continuous simulation modeling once upstream catchment date is available.

Table 8: Pre vs Post Development Flow Rates

Design Storm		Pre-Development Flow (L/s)	Post-Development Flow (L/s)
1:2 year	5 min	95.4	87.5
	24 hour	6.14	5.63
1:100 year	5 min	224.5	206.0
	24 hour	11.3	10.4

To mitigate, cliff erosion concerns, 1215 m² of the landscaped area has been converted into rain gardens. The rain garden areas have been sized and designed as retention facilities that provide temporary storage for 50% of the rainfall volume in a 1:2 year storm event. A typical cross section of the rain garden is shown below in Figure 12.




Figure 12: Typical Rain Garden Detail

The rain gardens have been sized using Metro Vancouver Stormwater Source Control Guideline (2012) and rock trench depths are indicated on Drawing A3.2 in Appendix A. The layer of geotextile fabric at the base of the assembly prevents infiltration while the perforated drainpipe carries retained flows to the minor system at a controlled rate. The perforated drainpipe, orifice, and pipes tying into the minor system control the release into the existing system. As the system is currently at capacity, controlling the release rates is critical to the design. These sizing for the perforated drains and orifice are to be determined once the system can be model in conjunction with the downstream pipe flows in the existing minor system.

Growing medium and plant species are to be determined by UBC Landscape Architects and must comply with the approved list of rain garden species in Metro Vancouver Stormwater Source Control Guideline (2012). As per Metro Vancouver Guidelines, the growing medium must have a minimum hydraulic conductivity of 70mm/hr (2012). As indicated on Drawing A3.2 in Appendix A, concrete weirs are to be installed at 10m intervals along all rain gardens installed south of the intersection. The weirs promote uniform capture and prevent erosion of the growing medium along the rain gardens installed on

the sloped regions in front of Allard Hall. Weirs are to be installed as per the Metro Vancouver Stormwater Source Control Guideline (2012).

Additional landscaped areas indicated on Drawing A3.2 are to be hydro-seeded as per UBC landscape standards. As indicated in Section 5.0, permeable pavers will be installed around the truck apron of the roundabout. A detail for the truck apron is shown below in Figure 13. The depth of the sub-base will be established by the geotechnical sub-consultant once asphalt cores are taken to ensure the structure can accommodate the required ESAL loading and the desired hydraulic conductivity for stormwater capture.




Figure 13: Permeable Truck Apron Detail

6.4 Catchbasin Relocations

Due to the realignment of curbs in proximity to the intersection, 11 catchbasin will need to be relocated and five new catchbasin will be installed. The project team has completed an initial visual inspection of the exiting catchbasin and determined that two if the Type C twin catchbasins along East Mall are in good enough condition to be savaged and reused on-site. The remainder of the relocated catchbasin will need to be replaced during construction. The existing and proposed catchbasin layouts and sizing are presented in Drawing A3.1 and A3.2.

By adding five new catchbasin to the site, upgrading three single catchbasin to double catchbasin, the proposed design captures 30% more runoff volume than the pre-development condition. Furthermore, the catchbasins located at the base of each bike ramp will act as localized trap lows in high flow events. This will allow up to 0.15m of ponding to occur, significantly increasing capture rates at these locations during large storm events as shown by the capture curves presented in Figure 14.




Figure 14: Type C Catchbasin Capture Curves

Exiting ponding issues will be mitigated through milling and resurfacing of the top lift of asphalt tying into the catchbasins identified on Drawing A3.2. To help control subsurface drainage beneath the road structure, perimeter drains will be installed beneath all new curbs that tie into a new catchbasin. All proposed catchbasins use single or double standard 1.2m barrels with bike-proof Type C frame and covers. Catchbasins and perimeter drains are to be installed as per the most recent edition of the Municipal Master Design Specification.

6.5 On-site Stormwater Treatment and Detention

To mitigate the increased demand on the minor system due to increased stormwater capture through catchbasins and rain gardens, the proposed stormwater upgrades include the installation of an 800 m³ StormTank undergrad stormwater detention facility and Furthermore, to meet water quality objectives, a STC 9000 Stormceptor oil and grit separator will be installed upstream of the stormwater tank.



Figure 15: Double Trap StormTrap System
(StormTrap, 2011a)




Figure 16: Stormceptor Oil and Grit Separator System
(Imbrium Systems, 2015)

An extra bypass pipe will be installed in Manholes four and nine as shown on Drawing A3.2. By installing this bypass line at a lower invert than the exiting mainline, the bypass line will divert stormwater water collected upstream of Manhole 4 to be diverted through an STC 9000 Stormceptor oil and grit separator and to the stormwater detention tank. The STC 9000 is capable of treating 100% of the diverted stormwater runoff and removing 88% of the TSS content. PCSWMM Model results and a construction detail for the STC 9000 system are provided in Appendix D.

The 6 m by 45m by 3m StormTrap Double Trap detention facility has been sized to provide both flood protection and irrigation capacity. The modular precast system is made of designed with a duel exit pipe connecting to Manhole two (refer to Drawing A3.2) which limits the retained stormwater volume at 120 m³ for irrigation purposes during normal flow conditions and allow larger volumes to be retained for flood control during large storm events. This system will ensure that anticipated 680 m³ runoff from a 1:100 year storm event can be accommodated at all times. The installation of Stormceptor upstream of the detention facility will ensure water to the tank during high frequency, low intensity events is of sufficient quality to be recycled through a purple pipe system an used to irrigate the nearby rose garden and landscaped areas around the Chan Centre. The StormTrap system pre-qualified for LEED credits under the Sustainable Site, Water Efficiency and Material and Resources categories (StormTrap, 2011b).

7.0 Gateway Feature

The Bike Garden provides UBC with a gateway feature to campus that is functional, aesthetically attractive, and aligns with UBC's mission to promote sustainability. The Bike Garden provides secure storage for up to 84 bicycles near the campus core.. A key feature of the Bike Garden is the integration of the structure into the area's stormwater management strategy through its green roof and nearby rain gardens. The proposed design includes the structural design complete with enclosures, green roof and drainage details. The structure and surrounding landscaping is shown in Figure 17. Detailed structural plans and elevations of the structure may be found in Appendix A.




Figure 17: Bike Garden and Surroundings

7.1 Integration With UBC Planning Objectives

Justification for the design of the Bike Garden was provided by the following documents published by UBC: the UBC Transportation Plan, the UBC Vancouver Campus Plan, the UBC Land Use Plan, and the UBC 20-Year Sustainability Strategy. Policy C2 of the UBC Transportation Plan (2014) states that investments in bike racks and secure parking either under cover or in parkades shall be made a priority, and that a minimum of 25% of UBC's bike racks shall be covered. This policy refers to, and summarizes requirements outlined in the UBC Vancouver Campus Plan, and the UBC Land Use Plan. Also, the UBC 20-Year Sustainability Strategy makes it a goal to campus with restricted vehicular access by facilitating alternative means of transportation such as cycling. The use of a green roof covered bike parkade is an efficient way to support UBC policy and produce an aesthetically pleasing gateway feature that can be enjoyed by cyclist and non-cyclist members of the public.

7.2 Structural Design

The Bike Garden features elements of timber, glass, concrete, and steel. Structural steel framing was chosen as the main structural system due to the relatively heavy loads of the green roof, and the long spans required in creating the open space of the interior. The structure was designed according to the 2012 British Columbia Building Code (BCBC), and its corresponding relevant adopted materials standard including: CSA S16-09 Design of Steel Structures, CSA S136-12 North American Specification for the Design of Cold-Formed Steel Structural Members, and CSA A23.3-14 Design of Concrete Structures. As per BCBC 2012, the design life of the structure is 50 years.

The structure was modelled in SAP2000 with wind, seismic, snow, dead, and live loads as specified from the 2012 BCBC. The structural members were designed for the forces obtained from this model. Appendix E contains the structural calculations for the design of the joists, girders, columns, braces, and steel composite decking. Table 9 below summarizes the design loading (ULS is Ultimate Limit States and SLS is Serviceability Limit States).

Table 9: Summary of Design Loading

Load	Size
ULS Snow Load	1.31 <i>kPa</i>
SLS Snow Load	1.48 <i>kPa</i>
ULS Wind Load	0.38 <i>kPa</i>
SLS Wind Load	0.36 <i>kPa</i>
Deck Weight Dead Load	1.62 <i>kPa</i>
Joist Weight Dead Load	1.28 <i>kPa</i>
Soil Weight Dead Load	2.20 <i>kPa</i>
Girder Weight Dead Load	0.65 <i>kN/m</i>
Glass Wall Weight Dead Load	0.32 <i>kPa</i>
Column Weight Dead Load	1.26 <i>kN</i>
Earthquake Base Shear (Distributed Over Each Roof Dimension)	338 <i>kN</i>
Roof Live Load	1.00 <i>kPa</i>

A steel composite deck supports the green roof assembly, which is in turn is supported by steel wide-flange joists (W460x52) spanning east to west. These joists frame into W530x66 girders running north-south. The following Figure 18 outlines the steel framing of the roof.




Figure 18: Roof Framing Plan

These girders are continuous along the entire length of the structure and rest on top of the six Hollow Structural Steel (HSS) columns, which direct the gravity loads to the footings and, finally, the ground. The lateral resistance in the longitudinal direction of the structure is provided by HSS braces, which resist loads in compression and tension. Figure 19 shows the west elevation of the structure with the lateral bracing.




Figure 19: West Elevation

In the transverse direction, moment frames at each end of the structure provide lateral resistance to seismic and wind loads. The connections between all steel and concrete elements are to be designed by the steel fabricator based on the loads specified in the drawings. Details are provided in Appendix A and show the parapet framing on the roof and the retaining wall design on the south end of the structure. The retaining wall and footings can be designed in full once the geotechnical sub-consultant has provided the

relevant soil properties. The geotechnical consultant may require a site investigation to be completed prior to the start of construction. They may perform this investigation with boreholes.

7.3 Architectural, Landscape and Sustainability Considerations

The architectural design of the Bike Garden was inspired by the natural surroundings of the site, including both the terrain and the natural vegetation. Furthermore, the Bike Garden was designed to uphold UBC's vision of sustainability and green design. Taking advantage of the site's natural grade, the structure appears to emerge from the terrain with a gentle upward sloping roofline.




Figure 20: Bike Garden North West View

Architectural finishes are designed to match the material palate specified for UBC's Contemporary District in which it is situated (UBC, 2012). The vertical faces of the structure were left as open as possible, and filled in with glazing on the long sides. This maximizes the amount of natural light in the interior, thus reducing the need for artificial lighting, and reducing the electrical demand. The roof parapet and the soffit are clad in locally sourced cedar siding as detailed in Figure 21; the cedar siding was chosen to convey a contemporary west coast feeling.




Figure 21: Cedar Siding Detail

Due to the need to limit the amount of stormwater infiltration in the area, the Project Team developed a design that integrated the Bike Garden into the site's Stormwater Management Plan. The structure features a green roof that is designed to capture 90% of rainwater in a 1:2 year event. This excess water then flows from the roof is distributed to rain gardens adjacent to the structure. Any water not retained by the rain gardens is collected by a system of geotextile and perforated pipes, which connect to the main stormwater system.

Table 10 identifies plant species selected for the green roof. These species have been selected in accordance with BC Landscape Standard, current edition, Section 11 - Landscape over Structures, BC Standard for Extensive Green Roofs as per the UBC Technical Guidelines for Green Roofs (2015). These species maximize the water retention time for controlled release during a storm event while also minimizing the amount of required maintenance.

Table 10: Green Roof Planting Schedule

Planting Schedule	Sourced From
Bearskin Fescue	UBC Botanical Gardens
Blue Gamma Grass	
Blue Sedge	
Mountain Moss Sedum	

8.0 Construction Planning

The overall constructability of the intersection has been a key consideration throughout the design stages of the project. A number of considerations have been taken into account while developing the construction phasing and the traffic management strategies. These strategies are expected to simplify construction staging, help minimize construction costs, and achieve the desired timelines. This section presents four key aspects of construction planning: a detailed construction schedule and phasing plan, a pre-tender cost estimate, a comprehensive risk assessment and a stakeholder management plan

8.1 Construction Schedule

Detailed design work and tender preparation has been fast tracked to accommodate a May 1, 2016 Construction start date, as requested by UBC Campus and Community Planning. The project is now ready to go to tender on April 11, 2016. This accommodates a minimum two tender period, and approximately a week for bid evaluation and project award ahead of the May 1st construction start date.

Special consideration given to graduation ceremonies that are set to take place May 25th – May 27th and May 30th – June 1st, 2016 at the Chan Centre. To minimize conflicts between ongoing roadwork and the traffic surges associated with the graduation ceremonies, construction will be limited to the bike garden during the month of May with the roadworks beginning June 2, 2016. Such strategic construction phasing also provides the contractor more time for mobilization, site investigation and material procurement for the proposed roadwork. Van Augustine estimates a three-month period for all proposed roadwork and the associated utility work. An interim construction completion date of September XX will be written into the contract documents to ensure the intersection is operational before the start of the 2016 – 2017 school year.

With roadway constriction and landscaping completed by the first week of September, Construction Completion Certificate (CCC) inspections are scheduled to span all of September. All deficiencies reported during these inspections will be remediated promptly. After the issuance of the CCC, as-built surveys will be performed in October, following which as-built drawings will be delivered to UBC Campus and Community and MoTI. Key milestones for the tender and construction period are indicated in Table 11. A Gantt Chart and a with a detailed timeline of all construction activities is included in Appendix F.

Table 11: Key Project Milestones

Project Milestone	Start Date	Completion Date
IFT Review and Revisions	April 8, 2016	April 10, 2016
Tender Period	April 11, 2016	April 25, 2016
Contract Award	April 29, 2016	April 29, 2016
Gateway Construction	May 5, 2016	June 3, 2016
Roadway Construction	June 3, 2016	August 17, 2016
Site Landscaping	August 17, 2016	August 30, 2016
CCC Inspections and Deficiency Review	August 31, 2016	September 30, 2016
Construction Completion	October 3, 2016	October 31, 2016

8.2 Construction Staging Plan

A construction staging plan has been included in the tender package to provide clarity and guidance to constructors in establishing their construction bids. The staging plan will also be used to support stakeholder engagement activities. Construction sequencing takes has been established in accordance with UBC's Traffic Management Plan Guidelines for Events and Construction and aims to minimize lane closures and disruption during peak operating hours and maintain public safety at all times. Figure 22, provides an overview of the proposed construction sequencing.




Figure 22: Construction Phasing

Key aspects of the proposed staging strategy are identified below. Drawings have also been prepared for each phase of the road construction and are included in Appendix A.

- Work zones, as indicated on the phasing plans, has been limited to the minimum required 0.5m outside of the immediate construction area to minimize the need for lane closures and detours.
- A temporary detour road is to be constructed across the Chancellor Blvd. median to accommodate two way traffic along Chancellor Blvd. while the stormwater detention facility is installed.
- The contractor will be required to complete tasks that require single lane alternating traffic during non-peak hours only (between 10am and 3pm). During peak hours, the contractor must arrange the work zone in these stages to accommodate two-way traffic.
- Stakeholder engagement will take place throughout the duration of construction to ensure all intersection users and nearby residents and facilities are aware of changes to traffic and pedestrian patterns from one phase to the next.

The phasing strategy is designed to be a high level-planning tool for contractors. Upon contract award, the contractor will be required to submit a detailed Traffic Control Plan, Public Communication Plan, Incident Response Plan, and Implementation Plan. These documents must clearly indicate all necessary traffic and pedestrian detours, signage, temporary barriers and traffic management personal.

8.3 Pre-Tender Cost Estimate

The Class C cost estimate reported at the conclusion of the preliminary design stage has been revised to a construction ready version that is reflective of the features developed during the detailed design of the project. As per the summarized cost breakdown in Table 12, the project will be delivered, by September 2016, at a net cost of \$1.59 million.

Table 12: Pre-Tender Cost Estimate

Item	Description	Estimated Cost
P1	Development Permit	\$1,500
P2	Excavation & Backfill Permits	\$2,500
P3	Erosion and Sediment Control Permit	\$500
P4	Traffic Management Permit	\$500
P5	Building Permit for Bike Park Gateway	\$2,000
P6	Streets and Landscape Permit	\$500
Permitting Subtotal		\$7,500

..

Item	Description	Estimated Cost
C1	Mobilization, Demobilization and Removals	\$268,000
C2	Earthworks	\$23,000
C3	Concrete & Roadwork	\$284,925
C4	Detour Road	\$7,236
C5	Underground Works	\$113,300
C6	Temporary Traffic and Pedestrian Traffic Control	\$20,000
C7	Streetlighting	\$21,000
C8	Erosion & Sediment Control and Landscaping	\$131,700
C9	Bike Garden Construction	\$276,000
C10	Miscellaneous Items – Record Drawings	\$5,000
C11	Provisional Items	\$404,000
Construction Subtotal		\$1,448,800
E1	Engineering Fees – Contract Administration and Testing (10%)	\$144,880
Engineering & Project Management Subtotal		\$144,880
Total Estimate (2016 Dollars)		\$1,593,680
Annual Operation and Maintenance Costs (0.7%)		\$10,200

As shown in Table 12, the final estimate is based on a construction cost of \$1.45 million. A Schedule of Quantities and full breakdown of the Pre-Tender Cost Estimate can be found in Appendix G. Worth noting is that the final construction cost estimate includes provisional items worth \$404,000. The provisional items, which include a proposed underground stormwater management facility, are recommended, but optional and may be removed from the scope of work on the project owners' request. Furthermore, in keeping with MoTI guidelines, the contract administration fees for the construction phase have been estimated at 10% percent of the total construction cost.

In addition to the construction and engineering costs, the permitting costs for the project are estimated to be \$7,500. Required permits include a Development Permit for the overall Site, A Streets and Landscape Permit and a Building Permit for the Bike Garden. As the Bike Garden is to be used for bike storage only, the project is exempt from UBC's Infrastructure Impact Charge, Community Amenity Charge and Regional Sewerage Levy. The relevant permit application forms are included in Appendix H.

The principal revisions made to the cost estimate as part of the detailed design process are as follows:

- A refined estimate of the supply and install costs for the gateway feature – the Bike Garden.
- Adjustment of the costs to account for the fast-tracking of activities for individual construction phases.
- Refinement of construction cost associated with rain gardens around the Bike Garden.
- Updated quantities for the supply and install of new catch basins and manholes.
- A more accurate estimate of concrete, asphalt, and landscape addition and removal.
- Elimination of the contingency buffer.

For the post-construction period, the annual maintenance costs of the intersection are estimated at 0.7% of the net construction costs, in accordance with MoTI guidelines. Any uncertainty in quantities and project elements that remains at the time of tender will be accounted for as cash allowance items in the contract documents.

8.4 Risk Assessment

A comprehensive risk analysis has been completed as part of the construction planning process. Key project risks are outlined below. A complete Risk Register is included in Appendix I.

Table 13: Key Project Risks

Key Project Risks	Probability	Consequence
Pacific Spirit Park Encroachment	Medium	High
Permit and Crossing Agreement Delays	High	Medium
Runoff Catchment Size	High	Low
Deep Utility Elevations	Medium	High
Probability: Refers to likelihood of occurrence Consequence: Refers to impact to both project schedule and budget		

- **Pacific Spirit Park Encroachment:** Specific right-of-way information is not currently available for NW Marine Dr. The position of the inscribed circle of the roundabout has been optimized to minimize impact on adjacent properties however there may be a small amount of encroachment onto the Metro Vancouver property the existing curb alignments and the east-west property line shown on UBC base maps. This area is highlighted in red in Figure 23 below. While it is likely that the right-of-way actually extends beyond the construction limits, property encroachment will need to be confirmed during pre-construction site investigations. If property appropriation is required, the

schedule for proposed roadwork may suffer delays. However, the project team is confident that the benefits to Pacific Sprit Park in terms of safer access for park users and improved stormwater management far outweigh the minimal encroachment area and the probability that encroachment will become a major project issue has been rated as medium.




Figure 23: Possible Property Encroachment Area

- **Permit and Crossing Agreement Delays:** All proposed roadworks and developmental works are subject to permit processes. Thus, risks are associated with delays in permit deliveries. Due to the heavy density of underground utilities under the intersection, several parties will need to be coordinated with for obtaining permits for construction around their respective utilities. Specifically, Metro Vancouver, BC Hydro, FortisBC, and UBC operations will need to be consulted for: work around their shallow utilities, the grade adjustment of their manholes, the relocation of catch basins in the stormwater management system, and the extensions of the associated stormwater leads. Delays due to the permit application reviews and the associated inspections may also push roadworks schedule into September.
- **Runoff Catchment Size:** Since detailed topographic and pipe profile information is not available at this stage of the project, the stormwater modelling has been completed using localized catchment areas. There is a high likelihood that these catchment areas are undersized. To mitigate this risk, models have been executed using the required 1:2yr and 1:100 year at the 24 hour intensity level as well as the 5 min intensity. 5 min intensity level gives an overestimate of peak flow rates to provide

a conservative upper bound for the model. Furthermore, the underground stormwater detention facility has been sized using the 1:100 year flood volume estimated by Urban Systems using an overland flow model for the entire campus. Based on these mitigation measures, the risk consequence level has been rated as low.

- **Deep Utility Elevations.** In the design of the minor system it has been assumed that the proposed upgrades can be accommodated around the existing infrastructure. It is assumed that the existing manhole barrel depths and mainline inverts to accommodate the bypass system that directs water to the underground detention facility. If invert elevations or manhole depths are not able to support the proposed system, an alternative configuration will need to be design. The density of utilities and the intersection and integration of utility upgrades with each of the construction phases render this a medium probability and high consequence risk. Sequencing the roadworks after the completion of the Bike Garden helps mitigate this risk as the month of May is available for detailed utility survey and any necessary design revisions.

8.5 Stakeholder Engagement

Early and proactive stakeholder engagement is crucial to efficiently and sustainably executing the construction phase within the constraints of the project budget and schedule. The stakeholder registry created during the preliminary design phase to identify all project stakeholders is included in Appendix J. This document was used to tailor an engagement strategy to the particular interests and role of each stakeholder group.

As joint owners of the intersection right-of-way, MoTI and the Musqueam First Nation are key stakeholders in the tender review and final construction approval process. Based on current and past use of the site as part of the provincial road network, the project team does not anticipate any major objections to the project on behalf of the Musqueam First Nation. However, the pre-construction investigation will provide an opportunity to revisit historic use of the area and determine if the project area holds any special cultural significance for the Musqueam Indian Band. This assessment provides a forum to identify existing or future impacts and establish reconciliation measures in collaboration the Musqueam Indian Band, if necessary.

The preliminary design report proposed a comprehensive stakeholder engagement plan based on the project phasing, as illustrated in Figure. 24. The objectives and the timing of each engagement activity were carefully planned based on the anticipated project impacts as well as the interest and level of

influence of each stakeholder group central to the planned activity. The engagement plan is inclusive and ensures the right information gets distributed at the right time to keep the project on schedule. Phases 1, 2, and 3 have been completed through the conceptual, preliminary, and detailed design processes. Phase 4 and 5 will be ongoing throughout the construction process.




Figure 24: Stakeholder Engagement Plan

Key Aspects of the remaining stakeholder engagement phases include:

- **Phase 4 – Construction Information:** The project team will work with UBC to ensure all relevant construction information lane closures and detours are distributed to stakeholders in the days leading up to construction and at the start of every new construction stage. Nearby residents, intersection users and adjacent landowners or building occupants will be specifically targeted in this phase along with the information dissemination measures enacted for the general public through the project website.
- **Phase 5– Education Campaign:** While there are three existing roundabouts on UBC Campus, roundabouts are a fairly recent addition to the campus roadway network. Many jurisdictions in Canada have found that educating users prior to and during the first months of installation can reduce undesirable driver behaviour and complaints. Public education will be achieved through a combination of road signs, community flyers, web materials and staging construction. These measures will allow drivers to see the roundabout evolve and drive through it during construction. This phase will begin when road construction begins and will continue for the first four months of operation.

9.0 Closing

Van Augustine Consultants proposes a roundabout for the redesign of NW Marine Dr.-East Mall-Chancellor Blvd. intersection. The roundabout incorporates several features to improve intersection safety, operational efficiency, and sustainability. Most notably, roundabout geometry is optimized for safer use; proposed lane widths, turning and entry/exit radii are engineered for reduced traffic speeds. While reducing vehicular collision risk, slower traffic also makes the intersection safer for cyclists and pedestrians. Furthermore, the addition of a bike parking facility featuring a green roof is proposed as the gateway feature for the intersection. Named the Bike Garden, the structure will house 84 bikes and will reflect UBC's continued commitment to sustain green building design and alternate transport modes.

Overall, the redesigned intersection adds 910 m² of pervious area to the site and 1215 m² of landscaped area is converted to rain gardens to retain stormwater and mitigate existing cliff erosion issues north of the intersection. New catchbasins are also being added to increase stormwater capture. Most of the captured stormwater will be diverted through a Stormceptor Oil and Grit separator to an 800m³ underground stormwater detention facility located under Chancellor Blvd. east of the roundabout. This will allow for controlled release of stormwater into the already at-capacity stormwater network in the area. The storage tank also provides opportunity for utilizing any collected water for irrigation of the proposed as well as existing landscape

By the pre-tender cost estimate, this proposed redesign will require an investment of \$1.59 million for a September 2016 delivery. In terms of construction staging, Bike Garden construction begins May 1st, 2016, and roadwork begins June 3rd, 2016. This staging avoids potential conflicts between roadwork and the traffic surges associated with the annual UBC graduation ceremonies hosted at Chan Centre situated to the immediate southwest of the intersection. Additionally, all roadwork will be performed with comprehensive traffic management, and only periodic detours and partial closures. Finally, the redesigned intersection will be commissioned on September 1st, in time for the 2016-17 school year.

Van Augustine Consultants will continue to involve stakeholders in the final stages of design. Crossing agreement requests will be sent to utility providers and a meeting will be setup between the Ministry of Transportation and Infrastructure and Metro Vancouver to mitigate the right-of-way conflicts. In addition, the project team will also seek input on the construction staging plan from the stakeholders including nearby residents, intersection users, and nearby event facility managers. Their feedback will ensure that the construction of the new roundabout is efficient and user friendly. The stakeholder engagement plan

involves a public open house, an online feedback forum hosted on a public website with detailed information and periodic updates on the project.

Van Augustine Consultants have designed the project and planned the construction conservatively to mitigate risks and minimize impact to the schedule and budget. The proposed roundabout, stormwater management system, and Bike Garden will showcase UBC's goals and commitment towards sustainable and safe design to all those entering the campus.


References


- Bell, J. (2012). *Overland Flow Route Assessment – Final*. Vancouver: Urban Systems
- BC Landscape & Nursery Association, (2012). *BC Landscape Standard*. Surrey: BC Landscape & Nursery Association
- BC Ministry of Transportation and Infrastructure. (2013). *Project Cost Estimating Guidelines Version 01.02*. Project Management Support Services. Vancouver: BC Ministry of Transportation and Infrastructure.
- BCG Engineering Inc. (2009). *Metro Vancouver Regional IDF Curves, Metro Vancouver Climate Stations: Phase 1 Final*. Burnaby: Metro Vancouver.
- British Columbia Codes, (2012). *BC Building Code – 2012*. Victoria: Province of British Columbia.
- British Columbia Ministry of Water, Land and Air Protection, (2002). *Stormwater Planning: A Guidebook for British Columbia*. Victoria: Province of British Columbia.
- Bunt & Associates. (2016). *UBC CIVL 446 Presentation*. Vancouver: Bunt & Associates.
- CSA Group, (2009). *CAN/CSA S16-09 - Design of steel structures: Seventh Edition 2009*. Vancouver: CSA Group
- CSA Group, (2004). *CAN/CSA-A23.3-04 (R2010) - Design of Concrete Structures: Fifth Edition 2004*. Vancouver: CSA Group
- CSA Group, (2012). *CAN/CSA S136-12 - North American specification for the design of cold-formed steel structural members and S136.1-12 - Commentary on North American specification for the design of cold-formed steel structural members, 2012*. Vancouver: CSA Group
- Fisheries and Oceans Canada, (2001). *Urban Stormwater Management Guidelines*. Vancouver: Fisheries and Oceans Canada
- Geological Survey of Canada. (1998). *Geo-Map Vancouver*. Vancouver: Natural Resources Canada.
- Imbrium, (2015). *Stormceptor STC Technical Manual*. Imbrium Systems LLC.
- Kittleton Associates Inc. (2014). *Kansas Roundabout Guide: Second Edition 2014*. Kansas Department of Transportation.
- Lanac Consultants, Kerr Wood Leidel Associates Ltd. & Goya Ngan, (2012). *Stormwater Source Control Guidelines 2012*. Vancouver: Metro Vancouver.
- Ministry of Transportaion and Infrastructure (MoTI). (2015). *Pavement Strucutre Design Guidelines*. Geotechnical, Materials and Pavement Engineering. Vancouver: Government of British Columbia.
- Ministry of Transportaion and Infrastructure (MoTI). (2000). *Manual of Standard Traffic Signs and Pavement Markings*. Geotechnical, Materials and Pavement Engineering. Vancouver: Government of British Columbia.
- National Research Council Canada, (2010). *NRCC, National Building Code - Canada*, Ottawa: National Research Council Canada

- Russel, P. (2005). *A Sustainable Drainage Strategy for the South Campus Neighborhood*. Vancouver: Aplin & Martin Consultants Ltd. & Holland Barrs Planning Group Inc.
- StormTrap, (2011a). *StormTrap System Installation Guide*. Holcim: Humes Water Solutions.
- StormTrap, (2011b). *StormTrap LEED Contribution*. Retrieved March, 2016 from: <http://stormtrap.com/sustainability/leed-accreditation/>.
- University of British Columbia (UBC). (2006). *16th Avenue Consultaiton Report*. Campus and Community Planning. Vancouver: University of British Columbia.
- Univeristy of British Columbia (UBC). (2012). *UBC Campus Plan, Vancouver Campus*. The University of British Columbia, Vanouver. UBC.
- Univeristy of British Columbia (UBC). (2014a). *Integrated Stromwater Managmenet Plan*. The University of British Columbia, UBC Sustaibility and Engineering, UBC Campus + Community Planning. Vancouver: UBC.
- Univeristy of British Columbia (UBC). (2014a). *UBC Transportation Plan, Vancouver Campus*. The University of British Columbia, UBC Campus + Community Planning. Vancouver: UBC.
- University of British Columbia (UBC). (2014b). *UBC 20-Year Sustainability Strategy*. Vancouver: University of British Columbia.
- Univeristy of British Columbia (UBC), (2015). *Miscellaneous Sections (Section 02999): UBC Technical Guidelines – 2015 Edition*. Vancouver: University of British Columbia.
- Univeristy of British Columbia (UBC) Energy & Water Services, (2015). *UBC Catchments*. Retrived April, 2016 from: <http://energy.ubc.ca/ubcs-utility-infrastructure/storm-sewer/>
- WDO. (2013). *Waste Diversion Ontario's 2013 Stakeholder Engagement Plan*. Toronto: Waste Diversion Ontario.

APPENDIX A

IFT Drawing Set





Van Augustine Consultants

-----//-----

DRAWING REVISION:

ISSUE FOR CLIENT REVIEW	12/ 15
INTERMEDIATE DESIGN REVIEW 1	02/ 16
INTERMEDIATE DESIGN REVIEW 2	XX/ 15
ISSUED FOR BID	XX/ 15
ISSUED FOR CONSTRUCTION	XX/ 15

DRAWING TITLE

SIGNAGE AND TRAFFIC FLOW PLAN

SCALE:

1 : 750


PROJECT

CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN

SUBMISSION TITLE:

DETAILED DESIGN TEAM 5

DATE	A1
APRIL 2016	




DRAWING REVISION:	
ISSUE FOR CLIENT REVIEW	12/ 15
INTERMEDIATE DESIGN REVIEW 1	XV/ 16
INTERMEDIATE DESIGN REVIEW 2	XV/ 16
ISSUED FOR BID	XV/ 16
ISSUED FOR CONSTRUCTION	XV/ 16

DRAWING TITLE	
GEOMETRIC DESIGN AND CURB LAYOUT PLAN	
SCALE:	
1 : 750	
PROJECT	
CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN	

SUBMISSION TITLE:	
DETAILED DESIGN TEAM 5	

DATE	A2
APRIL 2016	



- LEGEND**
- EXISTING WATERLINE
 - EXISTING SANITARY MAIN LINE
 - EXISTING STORM MAIN LINE
 - PROPOSED SUBDRAINS
 - PROPOSED STORM BYPASS LINE
 - PROPOSED CATCH BASIN LEAD
 - STORMCEPTOR
 - PROPOSED CATCHBASIN
 - EXISTING CATCHBASIN
 - PROPOSED STM MANHOLE
 - EXISTING STM MH
 - EXISTING SAN MH
 - PROPOSED HYDROSEED AREA
 - PROPOSED RAIN GARDEN
 - PROPOSED GREEN ROOF

CB / MH ID	TYPE	SIZE	CHANGE FROM EXISTING
CB 1A	TYPE C	SINGLE	COLLAR REALIGNMENT
CB 1B	TYPE C	SINGLE	ADJUST TO FINISH GRADE
CB 2A	TYPE C	SINGLE	SUPPLY & INSTALL
CB 3A	TYPE C	SINGLE	SUPPLY & INSTALL
CB 4A	TYPE C	TWIN	INSTALL SALVAGED TWIN CB
CB 5A	TYPE C	SINGLE	SUPPLY & INSTALL
CB 6A	TYPE C	SINGLE	SUPPLY & INSTALL
CB 6B	TYPE C	SINGLE	SUPPLY & INSTALL
CB 7A	TYPE C	TWIN	INSTALL SALVAGED TWIN CB
CB 7B	TYPE C	TWIN	SUPPLY & INSTALL
CB 7C	TYPE C	TWIN	ADJUST TO FINISH GRADE
CB 7D	TYPE C	TWIN	ADJUST TO FINISH GRADE
CB 9A	TYPE C	SINGLE	SUPPLY & INSTALL
CB 9B	TYPE C	TWIN	SUPPLY & INSTALL
CB 9C	TYPE C	SINGLE	SUPPLY & INSTALL
CB 10A	TYPE C	TWIN	SUPPLY & INSTALL
CB 10B	TYPE C	TWIN	SUPPLY & INSTALL
CB 10C	TYPE C	SINGLE	SUPPLY & INSTALL
STM MH 1	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 2	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 3	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 4	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 5	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 6	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 7	TYPE SA	STANDARD	ADJUST TO FINISH GRADE
STM MH 8	TYPE SA	STANDARD	-
STM MH 9	TYPE SA	STANDARD	SUPPLY & INSTALL
STM MH 10	TYPE SA	STANDARD	SUPPLY & INSTALL

Van Augustine Consultants

DRAWING REVISION:

ISSUE FOR CLIENT REVIEW	12/ 15
INTERMEDIATE DESIGN REVIEW 1	XV/ 16
INTERMEDIATE DESIGN REVIEW 2	XV/ 16
ISSUED FOR BID	XV/ 16
ISSUED FOR CONSTRUCTION	XV/ 16

DRAWING TITLE

EXISTING STORM WATER SYSTEM

SCALE:

1 : 750

PROJECT

CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN


SUBMISSION TITLE:

DETAILED DESIGN TEAM 5

DATE

APRIL 2016

A3.1



DRAWING REVISION:

ISSUE FOR CLIENT REVIEW	12/ 15
INTERMEDIATE DESIGN REVIEW 1	XV/ 16
INTERMEDIATE DESIGN REVIEW 2	XV/ 16
ISSUED FOR BID	XV/ 16
ISSUED FOR CONSTRUCTION	XV/ 16

DRAWING TITLE
**PROPOSED STORM WATER
MANAGEMENT PLAN**


SCALE:
1 : 750

PROJECT
**CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN**

SUBMISSION TITLE:
**DETAILED DESIGN
TEAM 5**

DATE
APRIL 2016

A3.2



DRAWING REVISIONS:	
ISSUE FOR CLIENT REVIEW 1	X07/16
INTERMEDIATE DESIGN REVIEW 1	X07/16
INTERMEDIATE DESIGN REVIEW 2	X07/16
ISSUE FOR BID	X07/16
ISSUE FOR CONSTRUCTION	X07/16

DRAWING TITLE
PERMEABLE - IMPERMEABLE
SURFACES RATIO

SCALE:
1 : 750

PROJECT
CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN

SUBMISSION TITLE:
DETAILED DESIGN
TEAM 5

DATE	A4
APRIL 2016	

EXISTING CURB ———
CURB TO BE DEMOLISHED - - - - -
PROPOSED CURB ———
WORK ZONE BOUNDARY ■■■■■

CONTRACTOR TO DEMOLISH EXISTING CURBS, INSTALL
TEMPORARY ASPHALT AND TRAFFIC CONTROL, AS
REQUIRED

MAINTAIN EXISTING SIDEWALK WHERE POSSIBLE TO
ALLOW FOR PEDESTRIAN CROSSING

LIMIT OF CONSTRUCTION
MILLING LIMIT

NORTHWEST MARINE DRIVE

INSTALL TEMPORARY DETOUR
LANE FOR WESTBOUND TRAFFIC
TO CROSS EXISTING MEDIAN

INSTALL TEMPORARY
ASPHALT

LIMIT OF CONSTRUCTION
MILLING LIMIT

CHANCELLOR BOULEVARD

MAINTAIN EXISTING SIDEWALK WHERE POSSIBLE TO
ALLOW FOR PEDESTRIAN CROSSING

GATEWAY FEATURE AND RAIN
GARDEN CONSTRUCTED IN
PREVIOUS PHASE. FURTHER
LANDSCAPING NEAR RAIN
GARDEN REQUIRED.

NORTHWEST MARINE DRIVE

LIMIT OF CONSTRUCTION
MILLING LIMIT

EAST MALL

CHANCELLOR MEWS

INSTALL PROTECTION FENCE
AROUND EXISTING TREES
PRIOR TO CONSTRUCTION
OF BIKE GARDEN

LIMIT OF CONSTRUCTION
MILLING LIMIT

IONA DRIVE

Van Augustine Consultants



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/15
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

PHASE 3 REMOVALS AND
DETOUR ROAD CONST.

SCALE:

1 : 750

PROJECT

CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN

SUBMISSION TITLE:

DETAILED DESIGN
TEAM 5


DATE

APRIL 2016

A5

NORTH





CONTRACTOR TO DEMOLISH EXISTING CURBS, INSTALL TEMPORARY ASPHALT AND TRAFFIC CONTROL, AS REQUIRED
CONTRACTOR TO ENSURE MINIMUM 0.5 METER WORKING DISTANCE FROM ALL CURB INSTALLATIONS

MAINTAIN EXISTING SIDEWALK WHERE POSSIBLE TO ALLOW FOR PEDESTRIAN CROSSING

INSTALL TEMPORARY ASPHALT WHERE NECESSARY TO FACILITATE TRAFFIC FLOW DURING CONSTRUCTION PHASE

LIMIT OF CONSTRUCTION MILLING LIMIT

TEMPORARY LANE FOR WESTBOUND TRAFFIC TO CROSS EXISTING MEDIAN

LIMIT OF CONSTRUCTION MILLING LIMIT

STATION TRAFFIC CONTROL PERSONS ALONG TEMPORARY 2-WAY LANE. INSTALL TRAFFIC CONES AND TEMPORARY SIGNAGE WHERE APPLICABLE

EXCAVATE AND INSTALL BELOW GRADE STORMWATER RETENTION FACILITY AND STORMCEPTOR

MAINTAIN EXISTING SIDEWALK WHERE POSSIBLE TO ALLOW FOR PEDESTRIAN CROSSING

LIMIT OF CONSTRUCTION MILLING LIMIT

LIMIT OF CONSTRUCTION MILLING LIMIT

Van Augustine Consultants



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/15
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

PHASE 4 SOUTH
CHANCELLOR BLVD CONST.

SCALE:
1 : 750

PROJECT


CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN

SUBMISSION TITLE:

DETAILED DESIGN
TEAM 5


DATE
APRIL 2016

A6



Van Augustine Consultants

-----//-----



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/15
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

PHASE 5 EAST MALL CONSTRUCTION

SCALE:

1 : 750


PROJECT

CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN

SUBMISSION TITLE:


DETAILED DESIGN TEAM 5

DATE	A7
APRIL 2016	



Van Augustine Consultants

-----//-----



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/15
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

NW MARINE DRIVE CONSTRUCTION

SCALE:

1 : 750

PROJECT

CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN


SUBMISSION TITLE:


DETAILED DESIGN TEAM 5


DATE

APRIL 2016

A8



Van Augustine Consultants -----//-----	
	
DRAWING REVISIONS:	
ISSUE FOR CLIENT REVIEW 1	XX/ 16
INTERMEDIATE DESIGN REVIEW 1	XX/ 16
INTERMEDIATE DESIGN REVIEW 2	XX/ 16
ISSUE FOR BID	XX/ 16
ISSUE FOR CONSTRUCTION	XX/ 16
 DRAWING TITLE	
PHASE 7 ROUNDABOUT CONSTRUCTION	
SCALE:	
1 : 750	
PROJECT	
CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN	
SUBMISSION TITLE:	
DETAILED DESIGN TEAM 5	
DATE	A9
APRIL 2016	



Van Augustine Consultants

-----//-----

DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/15
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

PHASE 8, 9 N. CHANCELLOR BLVD & E. MALL CONST.

SCALE:

1 : 750

PROJECT

CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN

SUBMISSION TITLE:

DETAILED DESIGN TEAM 5

DATE	A10
APRIL 2016	



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/ 16
INTERMEDIATE DESIGN REVIEW 1	XX/ 16
INTERMEDIATE DESIGN REVIEW 2	XX/ 16
ISSUE FOR BID	XX/ 16
ISSUE FOR CONSTRUCTION	XX/ 16

DRAWING TITLE

ROADWAY CROSS SECTIONS

SCALE:
1 : 200

PROJECT


**CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN**

SUBMISSION TITLE:


**DETAILED DESIGN
TEAM 5**

DATE
APRIL 2016


A11



1
A11
FINISHED GRADE N-S ROADWAY SECTION
SCALE AS NOTED



2
A11
FINISHED GRADE E-W ROADWAY SECTION
SCALE AS NOTED



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

**BIKE GARDEN GREEN
ROOF ASSEMBLY**

SCALE:

1 : 10

PROJECT

**CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN**


SUBMISSION TITLE:

**DETAILED DESIGN
TEAM 5**

DATE

APRIL 2016

D1



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

**BIKE GARDEN GREEN
ROOF ASSEMBLY**

SCALE:

1 : 10

PROJECT

**CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN**


SUBMISSION TITLE:

**DETAILED DESIGN
TEAM 5**

DATE

APRIL 2016

D2



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1 XX/16

INTERMEDIATE DESIGN REVIEW 1 XX/16

INTERMEDIATE DESIGN REVIEW 2 XX/16

ISSUE FOR BID XX/16

ISSUE FOR CONSTRUCTION XX/16

DRAWING TITLE

BIKE GARDEN FOUNDATION
& CURTAIN WALL ASSEMBLY

SCALE:

1 : 10

PROJECT

CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN

SUBMISSION TITLE:

DETAILED DESIGN
TEAM 5

DATE

APRIL 2016

D3

ISSUE FOR CONSTRUCTION XX/16

D4



DRAWING REVISIONS:

ISSUE FOR CLIENT REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 1	XX/16
INTERMEDIATE DESIGN REVIEW 2	XX/16
ISSUE FOR BID	XX/16
ISSUE FOR CONSTRUCTION	XX/16

DRAWING TITLE

RAIN GARDEN
ASSEMBLIES

SCALE:
1 : 10

PROJECT
CHANCELLOR BLVD, EAST
MALL, NW MARINE DR
INTERSECTION DESIGN

SUBMISSION TITLE:

DETAILED DESIGN
TEAM 5

DATE
APRIL 2016

D5

WEIRS INSTALLED EVERY 10m AS
INDICATED ON PLAN

RAIN GARDEN ASSEMBLY:
ORGANIC MULCH
GROWING MEDIA
DRAINAGE ROCK RESERVOIR
GEOTEXTILE SEPARATION FABRIC
NATIVE SOIL


MAXIMUM 2:1 SLOPE


OVERFLOW INLET AT
CATCHBASIN


UNDERDRAIN OVERFLOW

PIPE TO CONNECT TO
STORM DRAINAGE SYSTEM

PERFORATED PERIMETER DRAINAGE
PIPE TO DRAIN TO STORMWATER
UTILITIES







www.vanaugustineconsultants.com/

[illegible]

Project number	0001
Date	08/04/2016
Drawn by	KM/DW
Checked by	GVA

Scale 1 : 40



Project number	0001
Date	08/04/2016
Drawn by	KM/DW
Checked by	GVA
S3	
Scale	1 : 50

APPENDIX B

Site Photos

Site Visit – September 21, 2015






Site Visit – February 2, 2016





APPENDIX C


Conceptual Design Options



PROJECT
CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN
DRAWING TITLE:
CONCEPTUAL DESIGN TEAM 5
DATE
OCTOBER 2015

NOTES:


- 1. ALL LANES 3.7M WIDE MINIMUM
- 2. BIKE LANES 1.5M WIDE TYP
- 3. ALL MOVEMENTS ACCOMODATE WB-17
- 4. EAST-WEST MOVEMENTS ACCOMODATE WB-20



PROJECT
CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN
DRAWING FILE: FIGURE 4
CONCEPTUAL DESIGN TEAM 5
DATE
OCTOBER 2015

NOTES:


1. STOP CONTROLLED INTERSECTION
2. ALL LANES 3.7M WIDE MINIMUM
3. BIKE LANES 1.5M WIDE TYP
4. ALL MOVEMENTS ACCOMODATE WB-17
5. EAST-WEST MOVEMENTS ACCOMODATE WB-20



PROJECT
CHANCELLOR BLVD, EAST MALL, NW MARINE DR INTERSECTION DESIGN
DRAWING FILE:
CONCEPTUAL DESIGN TEAM 5
DATE
OCTOBER 2015

APPENDIX D


Stormwater Design



INLET CAPTURE DATA


Catchbasins under Flow-By Conditions (with no ICD)

TYPE C & K		
Qapp (l/s)	Qcap (l/s)	Capture Efficiency %
0	0	
9	9	100%
15	13	85%
25	17	66%
50	23	46%
75	28	38%
100	33	33%
200	48	24%
300	61	20%
500	79	16%
1000	104	10%



Catchbasins under Ponding Conditions (with no ICD)

Ponding Depth (m)	Capture Rate (l/s)	
	Single Type C	Double Type C
0.00	0	0
0.10	110	201
0.20	150	210
0.30	156	218
0.40	161	226
0.50	166	233



Catchbasin Capture for High Intensity Rain Event - 1:100yr, 5min									
Catchment	Ha	Total # of CBs	Runoff (L/s)	Runoff (L/s/ha)	inlets/ha	Qapp (L/s/inlet)	Q Capture/inlet	Q capture - Total (L/s)	Capture Efficiency
Pre-Development									
N	0.1161	0	29.11	250.69	0.0	0.0	0.00	0.000	
E	0.4363	5	81.43	186.63	11.5	37.3	10.37	51.845	
S	0.4549	6	61.92	136.12	13.2	22.7	7.48	44.874	
W	0.2868	1	52.02	181.39	3.5	181.4	36.09	36.086	
Total	1.2941	12	224.476					132.805	59%
N	0.1161	1	29.11	250.74	8.6	62.7	15.55	15.554	
E	0.4363	6	75.58	173.23	13.8	28.9	11.01	66.038	
S	0.4549	6	52.83	116.14	13.2	19.4	9.11	54.688	
W	0.2868	4	48.43	168.87	13.9	42.2	13.62	54.493	
Total	1.2941	17	205.959					190.773	93%
							Increase in Capture Efficiency		33%
							Additional Water Captures		30%

Detailed Stormceptor Sizing Report – UBC

Project Information & Location			
Project Name	UBC Intersection Redesign	Project Number	487
City		State/ Province	British Columbia
Country	Canada	Date	2/28/2016
Designer Information		EOR Information (optional)	
Name	Janet Jorgensen	Name	
Company	UBC	Company	
Phone #	778-874-2315	Phone #	
Email	janetjorgensen@gmail.com	Email	

Stormwater Treatment Recommendation

The recommended Stormceptor Model(s) which achieve or exceed the user defined water quality objective for each site within the project are listed in the below Sizing Summary table.

Site Name	UBC
Recommended Stormceptor Model	STC 9000
Target TSS Removal (%)	85.0
TSS Removal (%) Provided	88
PSD	City of Victoria PSD
Rainfall Station	VANCOUVER - KITSILANO HI

The recommended Stormceptor model achieves the water quality objectives based on the selected inputs, historical rainfall records and selected particle size distribution.

Stormceptor Sizing Summary		
Stormceptor Model	% TSS Removal Provided	% Runoff Volume Captured Provided
STC 300	55	95
STC 750	67	99
STC 1000	69	99
STC 1500	69	99
STC 2000	73	100
STC 3000	75	100
STC 4000	80	100
STC 5000	81	100
STC 6000	83	100
STC 9000	88	100
STC 10000	88	100
STC 14000	91	100
Stormceptor MAX	Custom	Custom

Stormceptor

The Stormceptor oil and sediment separator is sized to treat stormwater runoff by removing pollutants through gravity separation and flotation. Stormceptor's patented design generates positive TSS removal for each rainfall event, including large storms. Significant levels of pollutants such as heavy metals, free oils and nutrients are prevented from entering natural water resources and the re-suspension of previously captured sediment (scour) does not occur.

Stormceptor provides a high level of TSS removal for small frequent storm events that represent the majority of annual rainfall volume and pollutant load. Positive treatment continues for large infrequent events, however, such events have little impact on the average annual TSS removal as they represent a small percentage of the total runoff volume and pollutant load.

Design Methodology

Stormceptor is sized using PCSWMM for Stormceptor, a continuous simulation model based on US EPA SWMM. The program calculates hydrology using local historical rainfall data and specified site parameters. With US EPA SWMM's precision, every Stormceptor unit is designed to achieve a defined water quality objective. The TSS removal data presented follows US EPA guidelines to reduce the average annual TSS load. The Stormceptor's unit process for TSS removal is settling. The settling model calculates TSS removal by analyzing:

- Site parameters
- Continuous historical rainfall data, including duration, distribution, peaks & inter-event dry periods
- Particle size distribution, and associated settling velocities (Stokes Law, corrected for drag)
- TSS load
- Detention time of the system

Hydrology Analysis

PCSWMM for Stormceptor calculates annual hydrology with the US EPA SWMM and local continuous historical rainfall data. Performance calculations of Stormceptor are based on the average annual removal of TSS for the selected site parameters. The Stormceptor is engineered to capture sediment particles by treating the required average annual runoff volume, ensuring positive removal efficiency is maintained during each rainfall event, and preventing negative removal efficiency (scour). Smaller recurring storms account for the majority of rainfall events and average annual runoff volume, as observed in the historical rainfall data analyses presented in this section.

Rainfall Station

State/Province	British Columbia	Total Number of Rainfall Events	5128
Rainfall Station Name	VANCOUVER - KITSILANO HI	Total Rainfall (mm)	24905.7
Station ID #	4201	Average Annual Rainfall (mm)	1245.3
Coordinates	49°15'N, 123°9'W	Total Evaporation (mm)	1241.4
Elevation (ft)		Total Infiltration (mm)	10472.5
Years of Rainfall Data	20	Total Rainfall that is Runoff	13191.8

Notes

- Stormceptor performance estimates are based on simulations using PCSWMM for Stormceptor, which uses the EPA Rainfall and Runoff modules.
- Design estimates listed are only representative of specific project requirements based on total suspended solids (TSS) removal defined by the selected PSD, and based on stable site conditions only, after construction is completed.
- For submerged applications or sites specific to spill control, please contact your local Stormceptor representative for further design assistance.

Drainage Area		Up Stream Storage	
Total Area (ha)	1.29	Storage (ha-m)	Discharge (cms)
Imperviousness %	58.0	0.020	0.000
Water Quality Objective		Up Stream Flow Diversion	
TSS Removal (%)	85.0	Max. Flow to Stormceptor (cms)	
Runoff Volume Capture (%)	90.00	Design Details	
Oil Spill Capture Volume (L)		Stormceptor Inlet Invert Elev (m)	
Peak Conveyed Flow Rate (L/s)		Stormceptor Outlet Invert Elev (m)	
Water Quality Flow Rate (L/s)		Stormceptor Rim Elev (m)	
		Normal Water Level Elevation (m)	
		Pipe Diameter (mm)	
		Pipe Material	
		Multiple Inlets (Y/N)	Yes
		Grate Inlet (Y/N)	No


Particle Size Distribution (PSD)		
Removing the smallest fraction of particulates from runoff ensures the majority of pollutants, such as metals, hydrocarbons and nutrients are captured. The table below identifies the Particle Size Distribution (PSD) that was selected to define TSS removal for the Stormceptor design.		
City of Victoria PSD		
Particle Diameter (microns)	Distribution %	Specific Gravity
3.0	10.0	2.65
10.0	23.0	2.65
33.0	25.0	2.65
67.0	11.0	2.65
100.0	12.0	2.65
333.0	11.0	2.65
500.0	8.0	2.65

Site Name		UBC	
Site Details			
Drainage Area		Infiltration Parameters	
Total Area (ha)	1.29	Horton's equation is used to estimate infiltration	
Imperviousness %	58.0	Max. Infiltration Rate (mm/hr)	61.98
Surface Characteristics		Min. Infiltration Rate (mm/hr)	10.16
Width (m)	227.00	Decay Rate (1/sec)	0.00055
Slope %	2	Regeneration Rate (1/sec)	0.01
Impervious Depression Storage (mm)	0.508	Evaporation	
Pervious Depression Storage (mm)	5.08	Daily Evaporation Rate (mm/day)	2.54
Impervious Manning's n	0.015	Dry Weather Flow	
Pervious Manning's n	0.25	Dry Weather Flow (lps)	0
Maintenance Frequency		Winter Months	
Maintenance Frequency (months) >	12	Winter Infiltration	0
TSS Loading Parameters			
TSS Loading Function			
Buildup/Wash-off Parameters		TSS Availability Parameters	
Target Event Mean Conc. (EMC) mg/L		Availability Constant A	
Exponential Buildup Power		Availability Factor B	
Exponential Washoff Exponent		Availability Exponent C	
		Min. Particle Size Affected by Availability (micron)	


Cumulative Runoff Volume by Runoff Rate			
Runoff Rate (L/s)	Runoff Volume (m³)	Volume Over (m³)	Cumulative Runoff Volume (%)
1	51.362	119.671	30.0
4	131.807	39.214	77.1
9	161.507	9.507	94.5
16	168.871	2.125	98.8
25	170.339	0.656	99.6
36	170.755	0.24	99.9
49	170.888	0.107	99.9
64	170.939	0.056	100.0

Cumulative Runoff Volume by Runoff Rate

For area: 1.29(ha), imperviousness: 58.0%, rainfall station: VANCOUVER - KITSILANO HI



Rainfall Event Analysis				
Rainfall Depth (mm)	No. of Events	Percentage of Total Events (%)	Total Volume (mm)	Percentage of Annual Volume (%)
6.35	4012	78.2	6090	24.5
12.70	555	10.8	5038	20.2
19.05	275	5.4	4288	17.2
25.40	119	2.3	2641	10.6
31.75	63	1.2	1790	7.2
38.10	43	0.8	1499	6.0
44.45	16	0.3	664	2.7
50.80	10	0.2	475	1.9
57.15	15	0.3	806	3.2
63.50	5	0.1	296	1.2
69.85	3	0.1	196	0.8
76.20	3	0.1	219	0.9
82.55	3	0.1	240	1.0
88.90	1	0.0	86	0.3
95.25	2	0.0	182	0.7
101.60	0	0.0	0	0.0
107.95	1	0.0	104	0.4
114.30	0	0.0	0	0.0
120.65	1	0.0	120	0.5
127.00	0	0.0	0	0.0
133.35	0	0.0	0	0.0
139.70	0	0.0	0	0.0
146.05	0	0.0	0	0.0
152.40	0	0.0	0	0.0
158.75	0	0.0	0	0.0
165.10	0	0.0	0	0.0
171.45	1	0.0	170	0.7
177.80	0	0.0	0	0.0
184.15	0	0.0	0	0.0





For Stormceptor Specifications and Drawings Please Visit:
<http://www.imbriumsystems.com/technical-specifications>

DRAWING NOT TO BE USED FOR CONSTRUCTION


THE STORMCEPTOR SYSTEM IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS:

United States Patent No. 5,753,115 • 5,849,181 • 6,068,765 • 6,371,690 • 7,582,216 • 7,666,303 | Australia Patent No. 693,164 • 707,133 • 729,096 • 779,401 • 289,647 • 2008,279,378 • 2008,288,900 | Canadian Patent No. 2,009,280 • 2,137,942 • 2,175,277 • 2,180,305 • 2,180,383 • 2,206,338 • 2,327,768 | Indonesian Patent No. 007058 | Japan Patent No. 3581233 • 9-11476 | Korea Patent No. 10-1451593 • 0519212 | Malaysia Patent No. 118987 | New Zealand Patent No. 314,646 • 583,583 • 583,008 | South African Patent No. 2010/00683 • 2010/01796 |



Stormceptor®

THE DESIGN AND INFORMATION SHOWN ON THIS DRAWING IS PROVIDED AS A SERVICE TO THE PROJECT OWNER, ENGINEER AND CONTRACTOR BY IMBRIUM SYSTEMS ("IMBRIUM"). NEITHER THIS DRAWING, NOR ANY PART THEREOF, MAY BE USED, REPRODUCED OR MODIFIED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF IMBRIUM. FAILURE TO COMPLY IS DONE AT THE USER'S OWN RISK AND IMBRIUM EXPRESSLY DISCLAIMS ANY LIABILITY OR RESPONSIBILITY FOR SUCH USE. IF DISCREPANCIES BETWEEN THE SUPPLIED INFORMATION UPON WHICH THE DRAWING IS BASED AND ACTUAL FIELD CONDITIONS ARE ENCOUNTERED AS SITE WORK PROGRESSES, THESE DISCREPANCIES MUST BE REPORTED TO IMBRIUM IMMEDIATELY FOR RE-EVALUATION OF THE DESIGN. IMBRIUM ACCEPTS NO LIABILITY FOR DESIGNS BASED ON MISSING, INCOMPLETE OR INACCURATE INFORMATION SUPPLIED BY OTHERS.

<div> www.imbrium.com</div> <div>605 GLOBAL WAY, SUITE 113, LINTHICUM, MD 21231</div> <div>USA 888-279-8826 CA 800-565-4801 INTL +1-416-960-9900</div>	OSR 9000 STANDARD MODEL ####		REV #	DATE	REVISION DESCRIPTION	BY	SHEET NUMBER 1 OF 1
DATE:#####		SCALE: 75	PROJECT No.: #####			DRAWN: ###	CHECKED: ###

APPENDIX E

Structural Design

Bike Garden Loading and Structural Framing Design

Loading (According to BCBC 2006)

Snow Load (1 in 50 year)

$$S_s := 1.8 \text{ kPa}$$

$$S_r := 0.2 \text{ kPa}$$

$$C_b := 0.8 \quad (\text{Small Roof - } I_c < 70\text{m})$$

$$I_{su} := 0.8 \quad (\text{ULS Low Importance Factor})$$

$$I_{ss} := 0.9 \quad (\text{SLS Low importance Factor})$$

$$C_w := 1.0$$

$$C_s := 1.0 \quad (\text{Roof Angle} = 2.9^\circ)$$

$$C_a := 1.0 \quad (\text{Standard Loading})$$

$$S_u := I_{su} \cdot (S_s \cdot (C_b \cdot C_w \cdot C_s \cdot C_a) + S_r) = 1.312 \text{ kPa} \quad (\text{ULS})$$

$$S_s := I_{ss} \cdot (S_s \cdot (C_b \cdot C_w \cdot C_s \cdot C_a) + S_r) = 1.476 \text{ kPa} \quad (\text{SLS})$$

Wind Load (1 in 50 year)

$$q := 0.48 \text{ kPa}$$

$$I_{wu} := 0.8 \quad (\text{ULS Low Importance Factor})$$

$$I_{ws} := 0.75 \quad (\text{SLS Low importance Factor})$$

$$l := 22.6 \text{ m} \quad (\text{Length})$$

$$w := 10 \text{ m} \quad (\text{Width})$$

$$h := (4800 + 2700) \cdot (0.5) \cdot 0.001 = 3.75 \text{ m} \quad (\text{Average Roof Height from Ground Level})$$

$$C_e := 0.7 \cdot \left(\frac{h}{12} \right)^{0.3} = 0.494$$

$$C_g := 2.0 \quad (\text{For Both External and Internal Pressures})$$

$$C_p := 1.0 \quad (\text{For Both External and Internal Pressures})$$

$$p_u := I_{wu} \cdot q \cdot C_e \cdot C_g \cdot C_p = 0.379 \text{ kPa} \quad (\text{ULS})$$

$$p_s := I_{ws} \cdot q \cdot C_e \cdot C_g \cdot C_p = 0.356 \text{ kPa} \quad (\text{SLS})$$

Dead Load

$$DL_D := 1.62 \text{ kPa} \quad (\text{Based on 38mm, 0.76mm thick Deck with 90mm Slab - Canam P-3615})$$

$$DL_J := 1.275 \text{ kPa} \quad (\text{Based on W460x52 Joists Spaced at 2.5m})$$

$$DL_S := 15.7 \frac{\text{kN}}{\text{m}^3} \cdot 140 \text{ mm} = 2.198 \text{ kPa} \quad (140\text{mm Soil Depth})$$

$$DL_G := 0.645 \frac{\text{kN}}{\text{m}} \quad (\text{Based on W530x66 Girders})$$

$$DL_{GI} := 0.320 \text{ kPa} \quad (\text{Based on Glass of 12mm Thickness})$$

$$DL_C := 0.279 \text{ kN} \cdot \text{m}^{-1} \cdot 4.5 \text{ m} = 1.256 \text{ kN} \quad (\text{Based on HSS127x127x8.0 of 4.5m Max. Height})$$

Earthquake Load (1 in 100 year)

$$A_R := l \cdot w = 226 \text{ m}^2 \quad (\text{Area of Roof})$$

$$A_W := l \cdot 3.75 \text{ m} = 84.75 \text{ m}^2 \quad (\text{Area of Wall Determined with the Average Roof Height})$$

$$N_G := 2 \quad (\text{Number of Girders})$$

$$N_C := 6 \quad (\text{Number of Columns})$$

$$DL_{Total} := (DL_D + DL_J + DL_S) \cdot A_R + DL_G \cdot N_G \cdot l + DL_C \cdot N_C + DL_{Gl} \cdot A_W \cdot 2 = (1.242 \cdot 10^3) \text{ kN}$$

$$W_{Total} := DL_{Total} + 0.25 \cdot S_u \cdot A_R = (1.316 \cdot 10^3) \text{ kN}$$

$$Sa_{0.2} := 0.94 \quad (\text{Seismic Data for Vancouver})$$

$$Sa_{0.5} := 0.64 \quad (\text{Seismic Data for Vancouver})$$

$$Sa_{1.0} := 0.33 \quad (\text{Seismic Data for Vancouver})$$

$$Sa_{2.0} := 0.17 \quad (\text{Seismic Data for Vancouver})$$

$$I_E := 0.8 \quad (\text{Low Importance Factor for both SLS and ULS})$$

$$F_a := 1.0 \quad (\text{Site Class C})$$

$$F_v := 1.0 \quad (\text{Site Class C})$$


Conservatively using 4.8 m as the height:

$$T_{AT} := 0.085 \cdot (4.8)^{0.75} = 0.276 \text{ s} \quad (\text{Transverse Direction Fundamental Period - Moment Frame})$$

$$T_{AL} := 0.025 \cdot 4.8 = 0.12 \text{ s} \quad (\text{Longitudinal Direction Fundamental Period - Braced Frame})$$

Since the structure is less than 60m in height and has a fundamental period of less than 2 seconds in each of the orthogonal directions, calculations may proceed using the equivalent static procedure.

Using the following graph to find the corresponding Acceleration:



$$S(T_{AT}) := 0.94 \quad (\text{Ground Acceleration for the Transverse Direction})$$

$$S(T_{AL}) := 0.89 \quad (\text{Ground Acceleration for the Longitudinal Direction})$$

$$R_d := 1.5 \quad (\text{Conventional Construction of Moment Frames, Braced Frames, or Shear Walls})$$

$$R_o := 1.3 \quad (\text{Conventional Construction of Moment Frames, Braced Frames, or Shear Walls})$$

$$M_V := 1.0 \quad (S_a(0.2)/S_a(2.0) < 8 \text{ and } T_a < 1.0 \text{ for Both Directions})$$

$$V_{Min} := \frac{(S_{a2.0} \cdot M_V \cdot I_E \cdot W_{Total})}{R_d \cdot R_o} = 91.788 \text{ kN}$$

$$V_{Max} := \frac{\left(\frac{2}{3} \cdot S_{a0.2} \cdot I_E \cdot W_{Total}\right)}{R_d \cdot R_o} = 338.354 \text{ kN}$$

$$V_T := \frac{(S(T_{AT}) \cdot M_V \cdot I_E \cdot W_{Total})}{R_d \cdot R_o} = 480.535 \text{ kN}$$

$$V_L := \frac{(S(T_{AL}) \cdot M_V \cdot I_E \cdot W_{Total})}{R_d \cdot R_o} = 480.535 \text{ kN}$$

Since the base shear for both transverse and longitudinal directions are larger than Vmax, the base shear in both directions is:

$$V := V_{Max} = 338 \text{ kN}$$

Since the structure is only one storey, the base shear is equal to the total lateral load at the roof in each span direction.

Live Load

$$LL := 1.0 \text{ kPa} \quad (\text{For Roofs})$$

Summary of Loading

$S_u = 1.312 \text{ kPa}$	(ULS Snow Load)
$S_s = 1.476 \text{ kPa}$	(SLS Snow Load)
$p_u = 0.379 \text{ kPa}$	(ULS Wind Load)
$p_s = 0.356 \text{ kPa}$	(SLS Wind Load)
$DL_D = 1.62 \text{ kPa}$	(Deck Weight DL)
$DL_J = 1.275 \text{ kPa}$	(Joist Weight DL)
$DL_S = 2.198 \text{ kPa}$	(Soil Weight DL)
$DL_G = 0.645 \text{ kN} \cdot \text{m}^{-1}$	(Girder Weight DL)
$DL_{Gl} = 0.32 \text{ kPa}$	(Glass Wall Weight DL)
$DL_C = 1.256 \text{ kN}$	(Column Weight DL)
$V = 338 \text{ kN}$	(Earthquake Base Shear to be Distributed Over Each Roof Dimension)
$LL = 1.000 \text{ kPa}$	(Roof LL)

Member Design

Deck Design

Load Case 3 Governs; 1.25 DL Factor Increased to 1.50 for Soil:

$$1.5 \cdot DL_S + 1.5 \cdot S_u + 0.5 \cdot LL = 5.765 \text{ kPa}$$

Based on the Canam Joist Catalog, the P-3615 Composite Deck of a 0.76mm thickness and 90mm thick slab has a capacity of 6.42 kPa for a 3m clear span, which is greater than the factored dead load of 5.765 kPa.

The self weight of this product is 1.62 kPa which is the same as the assumed weight of the deck and slab. Therefore, this product is acceptable. Note that the slab thickness of 90mm is taken from the bottom of the steel deck.

Use Canam P-3615 38mm (0.76mm Thick) Steel Deck with 90mm 20 MPa Concrete Slab and 10M Bars at 400mm each way, mid-height for crack control.

Joist Design

Bending Resistance Check:

Load Case 3 Governs; 1.25 DL Factor Increased to 1.50 for Soil:

$$1.5 \cdot (DL_S) + 1.25 \cdot (DL_D) + 1.5 \cdot S_u + 0.5 \cdot LL = 7.79 \text{ kPa}$$

Total Uniformly Distributed Factored Load (Joists Spaced at 2.5m):

$$7.79 \text{ kPa} \cdot 2500 \text{ mm} = 19.475 \frac{\text{kN}}{\text{m}}$$

Total of the Uniformly Distributed Factored Load (Unsupported Length of 10m):

$$19.475 \frac{\text{kN}}{\text{m}} \cdot 10 \text{ m} = 194.75 \text{ kN}$$

Based on the Handbook of Steel Construction pg. 5-131, a W460x52 joist can carry a total factored load of 271 kN, which is greater than the total factored load, above.

Shear Resistance Check:

$$\text{Shear Load} = 19.475 \frac{\text{kN}}{\text{m}} \cdot \frac{w}{2} = 97.375 \text{ kN}$$

Based on the Handbook of Steel Construction pg. 5-131, a W460x52 joist can carry a total factored load of 680 kN, which is greater than the above factored shear load.

Deflection Check:

$$\text{Deflection Limit} = \frac{w}{180} = 55.556 \text{ mm}$$


Based on the Handbook of Steel Construction pg. 5-131, a W460x52 joist has an approximate deflection of 54 mm, which is less than the deflection limit.

Therefore, 10m W460x52 joists spaced at 2.5m has an acceptable resistance and deflection.

Use 350W W460x52 Joists Spaced at 2500 mm.

Girder Design

Each W530x66 girder will have point loads of 98 kN every 2.5m due to the joists, and point loads of 49 kN at each end of the girder due to the end joists. The girders were modelled as follows:




The reaction at the cantilever support is: $R1 := 268 \text{ kN}$

The reaction at the centre support is: $R2 := 473 \text{ kN}$

The reaction at the end support is: $R3 := 156 \text{ kN}$


The bending moment diagram is as follows, which a maximum factored moment of 434 kN-m:



Based on the Handbook of Steel Construction pg. 5-96, the moment resistance for an unsupported length of 2.5m (the girder is laterally supported every 2.5m by the joists), is 444 kN-m.

Since $M_r > M_f$, the beam has an adequate bending resistance.

The shear force diagram is as follows, which has a maximum factored shear of 194 kN:




Based on the Handbook of Steel Construction pg. 5-96, the shear resistance is 927 kN.

Since $V_r > V_f$, the beam has an adequate shear resistance.

The maximum deflection (based on the ULS factored loads) as shown in the following diagram is 32.4 mm.

Note that this deflection will be higher than the deflection from service loads.



The maximum permissible deflection based on the largest unsupported length of 10m is the same as for the joists, which is 56 mm.

Since the deflection from ULS factored loads is less than the deflection limit, the W530x66 girders are acceptable.

Use 350W W530x66 Girders.

Column Design

Based on the girder support reactions, the max factored load is:

$$Pf := R1 = 268 \text{ kN}$$

The largest column is 4.5m and is pin-pin supported ($k=1$). Therefore:

$$kL := 4500 \text{ mm}$$

Based on the Handbook of Steel Construction pg. 4-52, an HSS 127x127x8.0 has an axial resistance of:

$$Pr := 484 \text{ kN}$$

Since $Pr > Pf$, the column is acceptable.

Use 350W HSS 127x127x8.0 Columns.

Lateral Design


The frames are modelled in SAP2000 using the loads from page 3 with:

- Wind pressure applied on the south glass wall with half of the load spreading to the roof and the other half transferred to the ground.
- Both the roof component of the wind load and the earthquake load are distributed over the full length of the 22.5 m roof.
- All load cases are checked and the governing load case is discussed in these calculations.


After the SAP2000 analysis, it was found that Load Case 5 (1.0DL + 1.0EQ+ 0.5LLL) was the critical load case.

The following are the Moment Force, Shear Force, and Axial Force Diagrams of the structure:

Moment Force Diagram (Units in kN-m)



Shear Force Diagram (Units in kN)



Axial Force Diagram (Units in kN)



Based on the above three diagrams, the following are determined:

- The maximum moment developed in the girders from this load case is 321 kN-m, which is less than the previously determined moment of 444 kN-m.
- The maximum shear developed in the girders from this load case is 169 kN, which is less than the previously determined shear of 194 kN.
- The maximum axial force developed in the HSS columns is 331 kN from this load case, which is more than the previously determined axial load of 268 kN, but less than the axial resistance of the columns of 484 kN.
- The maximum axial load in the braces is 102.43 kN.
- The maximum axial load in the girders is 86 kN.

Therefore:

- The columns are adequate for this load case,
- The girders need to be checked for combined axial and bending (Af = 86 kN, Mf = 321 kN-m for this load case),
- And the braces need to be designed for an axial load of 102.43 kN.

Girder Axial Compression and Bending Check

Axial resistance calculated from CSA S16-09:

$$\phi_s := 0.9$$

$$A_G := 8370 \text{ mm}^2 \quad (\text{Area of Girder: W530x66})$$

$$F_y := 350 \text{ MPa} \quad (350\text{W Steel})$$

$$E := 200000 \text{ MPa} \quad (\text{Modulus of Elasticity of Steel})$$

$$I_x := 351 \cdot 10^6 \text{ mm}^4 \quad (\text{Moment of Inertia for W530x66 About its X-Axis})$$

$$k := 1 \quad (\text{Pin-Pin})$$

$$l_{gird} := 2.5 \text{ m} \quad (\text{Laterally Supported by Joists at 2.5 m intervals})$$

$$r_x := 205 \text{ mm} \quad (\text{Radius of Gyration})$$

$$n := 1.34 \quad (\text{Hot-Rolled Structural Sections})$$

$$F_e := \frac{(3.14 \cdot E)}{\left(\frac{(k \cdot l_{gird})}{r_x}\right)^2} = (4.223 \cdot 10^3) \text{ MPa}$$

$$\lambda_a := 0$$

$$\lambda_b := \sqrt{\frac{F_y}{F_e}} = 0.288$$

$$C_f := 86 \text{ kN} \quad (\text{Axial Force from Load Case 5})$$

$$M_r := 444 \text{ kN} \cdot \text{m} \quad (\text{Moment Resistance from Page 5})$$

$$M_f := 321 \text{ kN} \cdot \text{m} \quad (\text{Moment Force from Load Case 5})$$

$$\omega_1 := 1.0 \quad (\text{Girder Subjected to Series of Point Loads})$$

$$C_e := \frac{(3.14^2 \cdot E \cdot I_x)}{l_{gird}^2} = (1.107 \cdot 10^5) \text{ kN}$$

$$U_{1x} := \frac{(\omega_1)}{\left(1 - \frac{C_f}{C_e}\right)} = 1.001$$

Cross-Sectional Strength:

$$C_{ra} := \phi_s \cdot A_G \cdot F_y \cdot \left(1 + \lambda_a^{2 \cdot n}\right)^{\frac{-1}{n}} = (2.637 \cdot 10^3) \text{ kN}$$

$$\frac{C_f}{C_{ra}} + \frac{(0.85 \cdot U_{1x} \cdot M_f)}{M_r} = 0.648$$

This value is less than one so the girder has an acceptable cross-sectional strength.

Overall Member Strength and Lateral Torsional Buckling Strength (Same Since k=1)

$$C_{rb} := \phi_s \cdot A_G \cdot F_y \cdot \left(1 + \lambda_b^{2 \cdot n}\right)^{\frac{-1}{n}} = (2.569 \cdot 10^3) \text{ kN}$$

$$\frac{C_f}{C_{rb}} + \frac{(0.85 \cdot U_{1x} \cdot M_f)}{M_r} = 0.648$$

This value is less than one so the girder has acceptable overall and lateral torsional buckling strengths.

Therefore, the **350W W530x66** column is acceptable under the loads from Load Case 5.

Brace Design

From the SAP2000 model, the maximum axial load in the braces is:

$$A_f := 102.43 \text{ kN}$$

From the Handbook of Steel Construction, Pg. 4-59:

$$A_r := 132 \text{ kN} \quad (\text{HSS } 152 \times 152 \times 4.8 \text{ for a length of } 11.2 \text{ m which is greater than the actual length is } 10.84 \text{ m, so this value is conservative})$$

Since $A_r > A_f$, the selected member is adequate. Therefore:

Use HSS 152x152x4.8 Braces

Diaphragm Design Check for Lateral Loads

For the diaphragm, it only needs to be designed for the lateral loads developed from wind or earthquake. For this structure, the governing load case is Load Case 5 (1.0*Earthquake):

$$V = 338.354 \text{ kN}$$

Distributing the Earthquake load over the length of the structure for the Transverse direction:

$$w_{et} := \frac{V}{l} = 14.971 \frac{kN}{m}$$

Distributing the Earthquake load over the width of the structure for the Longitudinal direction:

$$w_{el} := \frac{V}{w} = 33.835 \frac{kN}{m}$$

As before, use Canam P-3615 38mm (0.76mm Thick) Steel Deck with 90mm Concrete Slab.

For connections, refer to the SDI Diaphragm Design Manual 3rd Edition which specifies this design for the loading outlined above:

Current Diaphragm Resistance Check:

Unfactored Resistance of Diaphragm: 5595 plf

$$\phi_d := 0.5$$

$$S_r := \phi_d \cdot 5495 \text{ } plf = 40.097 \frac{kN}{m}$$

This is higher than the factored load from the earthquake as specified above (34 kN/m); therefore, the currently selected Canam diaphragm is adequate.

Side-Lap Connector Spacing

Spacing of connections should be the minimum of 5/span and 300mm. Therefore, for the side-lap connections, use #10 screws spaced at min (5/10m = 500, 300) = 300mm.

Perimeter Connector Spacing

$$\phi_d := 0.55$$

$$S_f := \frac{(w_{et} \cdot l)}{2 \cdot w} = 16.918 \frac{kN}{m} \quad (\text{Linear Load Along Edges from Transverse Earthquake Load})$$

$$Q_f := 7.08 \text{ } kN \quad (\text{Connector Resistance of Hilti ENP2})$$

$$sp := \frac{(\phi_d \cdot Q_f)}{S_f} = 230 \text{ } mm \quad (\text{Maximum Connector Spacing})$$

Therefore, use the current deck design with the following connection specifications:

- **Side Lap Connections with #10 Screws Spaced at 300mm**
- **Perimeter Connections with Hilti ENP2 Spaced at 225 mm**

Design Summary:

Deck:

Canam P-3615 38mm (0.76mm Thick) Steel Deck with 90mm Concrete Slab

Perimeter Connectors: Hilti ENP2 Spaced at 225 mm

Side-Lap Connectors: #10 Screws Spaced at 300 mm

Joists:

350W W460x52 10 m Long Joists Spaced at 2500 mm

Girders:

350W W530x66 22.5 m Long Girders

Columns:


350W HSS 127x127x8.0 Columns of Varying Height up to 4.5 m


Braces:

350W HSS 152x152x4.8 Braces

APPENDIX F

Construction Schedule





APPENDIX G

Pre-Tender Cost Estimate

Detailed Cost Estimate

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign

Client: UBC Campus + Community Planning

Owner: BC Ministry of Transportation

Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule A						
	<u>Site Preparation and Removals</u>					
Part 1 Mobilization/Demobilization						
1	Mobilization and Demobilization	L.S.	1	\$	10,000	\$ 10,000
2	Site Clearing and Grubbing	L.S.	1	\$	5,000	\$ 5,000
Subtotal Schedule A - Part 1 - Mobilization/Demobilization :					\$	15,000
Part 2 Removals and Relocation						
1	Sawcut, Remove & Dispose of Existing Concrete Curb and Gutter	m	1000	\$	20	\$ 20,000
2	Sawcut, Remove & Dispose of Existing Concrete Fill	m ²	600	\$	30	\$ 18,000
3	Sawcut, Remove & Dispose of Existing Concrete Sidewalk (including Wheelchair Ramp)	m ²	600	\$	30	\$ 18,000
4	Sawcut, Remove & Dispose of Existing Asphalt Pavement	m ²	1900	\$	30	\$ 57,000
5	Asphalt Milling (0-50mm Thickness)	m ²	4,000	\$	35	\$ 140,000
Subtotal Schedule A - Part 2 - Removals and Relocation:					\$	253,000
Total Schedule A - Site Preparation and Removals :					\$	268,000

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
Client: UBC Campus + Community Planning
Owner: BC Ministry of Transportation
Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule B	Earthworks					
Part 1	Grading					
1	Stripping (Typical 0.15mm Depth) - includes on-site stockpiling	m³	1,000	\$	6	\$ 6,000
2	Common Excavation (Cut-to-Fill)	m³	700	\$	10	\$ 7,000
3	Waste Excavation - Off-site Disposal	m³	350	\$	20	\$ 7,000
4	Subgrade Preparation for Road Structure	m²	1,000	\$	3	\$ 3,000
Subtotal Schedule B - Part 1 - Grading:					\$	23,000
Total Schedule B - Earthworks:					\$	23,000

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
Client: UBC Campus + Community Planning
Owner: BC Ministry of Transportation
Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule C	Concrete and Roadworks					
Part 1	Gravel					
1	25mm - Crushed Gravel Base (150mm Thick)	t	280	\$	36	\$ 10,080
2	75mm - Crushed Gravel Sub-Base (300mm Thick)	t	480	\$	30	\$ 14,400
Subtotal Schedule C - Part 1 - Gravel:					\$	24,480
Part 2	Asphalt Pavement					
1	Top Lift Asphalt - Hot-Mix Asphalt with PG 58-28 Binder and 30% RAP Content (50mm thick)	t	360	\$	140	\$ 50,400
2	Base Lift Asphalt - Hot-Mix Asphalt with PG 58-28 Binder and 30% RAP Content (300mm thick)	t	90	\$	138	\$ 12,420
3	Prime Coat	m²	4,000	\$	2	\$ 8,000
4	Tack Coat	m²	4,000	\$	2	\$ 8,000
Subtotal Schedule C - Part 2 - Asphalt Pavement:					\$	78,820
Part 3	Concrete Construction					
1	Concrete Standard Curb with 250mm Gutter	m	1,100	\$	60	\$ 66,000
2	Concrete Median/Island Fill	m²	75	\$	100	\$ 7,500
3	Supply and Install Concrete Sidewalk (2.00m width)	m	700	\$	150	\$ 105,000
5	Wheelchair Ramp	ea.	25	\$	125	\$ 3,125
Subtotal Schedule C - Part 3 - Concrete Construction:					\$	181,625
Total Schedule C - Concrete and Roadworks :					\$	284,925

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
 Client: UBC Campus + Community Planning
 Owner: BC Ministry of Transportation
 Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule D	<u>Detour Road</u>					
Part 1	Detour Road Grading					
1	Common Excavation (Cut-to-Fill)	m³	20	\$	20	\$ 400
2	Subgrade Preparation for Road Structure	m²	125	\$	6	\$ 750
Subtotal Schedule D - Part 1 - Detour Road Grading :					\$	1,150
Part 2	Detour Roadworks					
1	Asphalt Mix Type A with PG 58-31 Binder (140mm thick)	t	2	\$	125	\$ 250
2	25mm - Crushed Gravel Base (160mm Thick)	t	1	\$	36	\$ 36
3	Prime Coat	m²	125	\$	2	\$ 250
Subtotal Schedule D - Part 2 - Detour Roadworks :					\$	536
Part 3	Detour Road Removals					
1	Asphalt Removal	m²	125	\$	30	\$ 3,750
2	Waste Excavation - Off-site Disposal	m³	60	\$	30	\$ 1,800
Subtotal Schedule D - Part 3 - Detour Road Removals :					\$	5,550
Total Schedule D - Detour Road :					\$	7,236

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
 Client: UBC Campus + Community Planning
 Owner: BC Ministry of Transportation
 Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule E	<u>Underground Works</u>					
Part 1	Stormwater Infrastructure					
1	Supply and Install Type C Catch Basin	ea	17	\$	5,500	\$ 93,500
2	Existing Manhole Adjusted to Finished Grade	ea	17	\$	700	\$ 11,900
Subtotal Schedule E - Part 1 - Stormwater Infrastructure:					\$	93,500
Part 2	Adjustment of Roadway Appurtenances and Waterworks					
1	Existing Water Valve Adjusted to Finished Grade	ea	3	\$	1,000	\$ 3,000
2	Existing Manhole Adjusted to Finished Grade	ea	14	\$	350	\$ 4,900
Subtotal Schedule E - Part 2 - Adjustment of Roadway Appurtenances and Waterworks :					\$	7,900
Total Schedule E - Underground Works:					\$	113,300

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
 Client: UBC Campus + Community Planning
 Owner: BC Ministry of Transportation
 Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate	Extended Estimate Price
Schedule F	<u>Temporary Traffic and Pedestrian Traffic Control</u>				
Part 1	Temporary Traffic Control				
1	Lane Control Technicians, Construction Traffic Signs, and Traffic Management	L.S.	1	\$ 10,000	\$ 10,000
Subtotal Schedule F - Part 1 - Temporary Traffic Control :					\$ 10,000
Part 2	Temporary Pedestrian Traffic Control				
1	Supply and Implement Pedestrian and Cyclist Accommodation Plan and Implement Pedestrian Accommodation Measures	L.S.	1	\$ 10,000	\$ 10,000
Subtotal Schedule F - Part 2 - Temporary Pedestrian Traffic Control :					\$ 10,000
Total Schedule F - Temporary Traffic and Pedestrian Traffic Control :					\$ 20,000

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
Client: UBC Campus + Community Planning
Owner: BC Ministry of Transportation
Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price	
Schedule G	Streetlighting						
Part 1	Poles, Lights & Bases						
1	Relocation	ea	7	\$	3,000	\$	21,000
Subtotal Schedule G - Part 1 - Streetlighting:						\$	21,000
Total Schedule G - Streetlighting:						\$	21,000

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
 Client: UBC Campus + Community Planning
 Owner: BC Ministry of Transportation
 Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule H						
Erosion and Sediment Control & Landscaping						
Part 1						
ESC Measures						
1	Implement ESC Plan	L.S.	1	\$	10,000	\$ 10,000
2	Implementation of Tree Protection Plan	L.S.	1	\$	10,000	\$ 10,000
Subtotal Schedule H - Part 1 - ESC Measures:					\$	20,000
Part 2						
Landscaping						
1	Loam Respread	m²	2,900	\$	3	\$ 8,700
2	Seed - Hydroseed	m²	2,900	\$	2	\$ 5,800
3	Rain Gardens	m²	1,215	\$	80	\$ 97,200
Subtotal Schedule H - Part 2 - Landscaping:					\$	111,700
Total Schedule H - Erosion and Sediment Control & Landscaping:					\$	131,700

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
 Client: UBC Campus + Community Planning
 Owner: BC Ministry of Transportation
 Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule I	Gateway Structure: Bike Garden					
Part 1	Site Prepration					
1	Excavating and Grading	m³	120	\$	330.00	\$ 39,600
2	Landscaping	m²	500	\$	20	\$ 10,000
3	Green Roof	m²	225	\$	200	\$ 45,000
Subtotal Schedule I - Part 1 - Site Prepration:					\$	49,600
Part 2	Structural Erection					
1	Steel Members	kg	13000	\$	1.40	\$ 18,200
2	Supply and Install Concrete Foundation	m³	90	\$	150	\$ 13,500
3	Glass & Mullions	m²	80	\$	350	\$ 28,000
Subtotal Schedule I - Part 2 - Structural Erection:					\$	59,700
Total Schedule I - Gateway Structure: Bike Garden:					\$	286,000

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
Client: UBC Campus + Community Planning
Owner: BC Ministry of Transportation
Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate	Extended Estimate Price
Schedule J	<u>Miscellaneous Items</u>				
Part 1	Record Drawings				
1	Record Drawings	L.S.	1	\$ 5,000	\$ 5,000
Subtotal Schedule J - Part 1 - Record Drawings :				\$	5,000
Total Schedule J - Miscellaneous Items :				\$	5,000

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
 Client: UBC Campus + Community Planning
 Owner: BC Ministry of Transportation
 Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate		Extended Estimate Price
Schedule K						
	Provisional Items					
Part 1	Concrete Construction					
1	Fillcrete	m³	138	\$	100	\$ 13,800
Subtotal Schedule K - Part 1 - Concrete Construction :					\$	13,800
Part 2	Earthworks					
1	Imported Engineered Fill (Off-Site Source)	m³	60	\$	25	\$ 1,500
Subtotal Schedule K - Part 2 - Earthworks:					\$	1,500
Part 3	Underground Stormwater Detention Facility					
1	Excavation and Grading	L.S.	1	\$	50,000	\$ 50,000
2	Supply and Install (tank to accommodate 800m³ water)	L.S.	1	\$	275,000	\$ 275,000
3	Stormceptor	L.S.	1	\$	30,000	\$ 30,000
4	Irrigation Plumbing	L.S.	1	\$	50,000	\$ 50,000
Subtotal Schedule K - Part 3 - Underground Stormwater Detention Facility:					\$	405,000
Total Schedule K - Provisional Items :					\$	420,300

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
Client: UBC Campus + Community Planning
Owner: BC Ministry of Transportation
Consultant: Van Augustine Consultants

Date: April 8, 2016

Level of Estimate: Pre-Tender Estimate

Item	Description	Unit	Tendered Quantity	Engineer's Estimate	Extended Estimate Price
All Schedules Subtotal:					\$ 1,448,761
TOTAL TENDERED PRICE:					\$ 1,448,761

APPENDIX H

Permit Application Forms



THE UNIVERSITY OF BRITISH COLUMBIA
Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4

☎ 604.822.2633 • 📠 604.822.6119

BP # _____

Building Permit Application Form

Please submit completed Application Form and Building Permit Application Checklist to:
Campus and Community Planning

Building Address: _____	
Building Name: _____	
Building Number: _____	Development Permit #: _____
Legal Description: _____	
Type of Application: <input type="checkbox"/> Demolition <input type="checkbox"/> Alteration <input type="checkbox"/> Addition <input type="checkbox"/> New building <input type="checkbox"/> Relocation <input type="checkbox"/> Amendment <input type="checkbox"/> Other _____	

Owner Name / Authorized Agent Name:		Phone: _____	
		Email: _____	
Applicant name:		Phone: _____	
		Email: _____	
Mailing Address: _____			
City: _____	Province: _____	Postal Code: _____	Fax: _____

I HEREBY AGREE THAT I WILL COMPLY WITH ALL RULES, BYLAWS, REGULATIONS AND POLICIES OF THE UNIVERSITY OF BRITISH COLUMBIA AND ALL OTHER STATUTES, RULES, BYLAWS, POLICIES AND REGULATIONS OF OTHER AUTHORITIES IN FORCE AT THE UNIVERSITY OF BRITISH COLUMBIA RELATING TO THE WORK, UNDERTAKING OR PERMISSION IN RESPECT OF WHICH THIS APPLICATION IS MADE AND THAT I WILL INDEMNIFY AND SAVE HARMLESS THE UNIVERSITY OF BRITISH COLUMBIA, ITS OFFICIALS, EMPLOYEES AND AGENTS FROM ALL CLAIMS, LIABILITIES, JUDGEMENTS, COSTS OR EXPENSES OF EVERY KIND, INCLUDING NEGLIGENCE, IN RESPECT OF ANYTHING DONE OR NOT DONE IN CONSEQUENCE OF ANY PERMISSION, PERMIT OR LICENSE ISSUED AS A RESULT OF THE APPLICATION OR THE FAILURE TO OBSERVE COMPLETELY ALL STATUTES, RULES, BYLAWS, POLICIES AND REGULATIONS RELATING TO ANY WORK OR UNDERTAKING IN RESPECT OF WHICH THIS APPLICATION IS MADE.

SIGNED AT VANCOUVER, B.C. THIS _____ DAY OF _____ 20____

SIGNATURE OF AUTHORIZED AGENT: _____

Please continue application on reverse



THE UNIVERSITY OF BRITISH COLUMBIA
Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4

☎ 604.822.2633 • 📠 604.822.6119

Project Fees

All fees where applicable (Infrastructure Impact Charge (IIC), Community Amenity Charge (CAC), and Greater Vancouver Sewerage & Drainage District (GVSD) Development Cost Charge must be paid prior to the issuance of a Building Permit (see Building Permit Fee Schedule).

Submit calculations for all Fees.

Building Permit Fee

Contract Value*: \$	
Permit fee: \$	Amount enclosed: \$
Type: <input type="checkbox"/> Institutional <input type="checkbox"/> Non-Institutional	
Payment by: <input type="checkbox"/> Cheque** <input type="checkbox"/> Cash <input type="checkbox"/> PS Project#: _____ <input type="checkbox"/> BOW#: _____ - <input type="checkbox"/> Other: _____	
<p>* Refer to Building Permit Fee Schedule. Note: Contract values are required for each partial permit, if phased permits are requested.</p> <p>** All fees may be paid by cheque, money order or UBC internal requisition, payable to "University of British Columbia". Building Permit application fee is non-refundable.</p>	

Project Data for IIC and CAC Fee calculation*

☐ IIC

☐ CAC

☐ N/A

Building Area**: _____ ft ²	Amount: \$ _____
Net New Building Area: _____ ft ²	
Classification: <input type="checkbox"/> Market Housing _____ ft ²	<input type="checkbox"/> Institutional _____ ft ²
<input type="checkbox"/> Commercial _____ ft ²	<input type="checkbox"/> Industry Research _____ ft ²
<input type="checkbox"/> Separate Parking Structures _____ ft ²	
<p>* Academic Buildings are exempt</p> <p>** Refer to Building Area definition on IIC, CAC, and Regional Sewerage Levy</p>	

Project Data for Regional Sewerage Levy calculation

☐ Levy

☐ N/A

Unit Count: _____ Duplex(es)	_____ Townhouse(s)	_____ Apartment(s)
Non-Residential Use: _____ square feet	Total Amount: \$ _____	

In addition to fees, a refundable deposit in the amount of \$1000 per drawing for as-built drawings to a maximum of \$20,000 is required. Deposit will be returned upon receipt of satisfactory as-built drawings and the UBC 3D PlanMap model where applicable.



THE UNIVERSITY OF BRITISH COLUMBIA

Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4

☎ 604.822.2633 • 📠 604.822.6119

Building Permit Fee Schedule

Contract Value: The current monetary worth of the work described on the permit application and includes finishes, roofing, electrical, plumbing, drains, heating, air conditioning, fire extinguishing systems, elevators and other equipment or materials, construction management, contractor's profit and overhead, sales taxes (except goods and services taxes), insurance, the current monetary worth of contributed labour and materials and a reasonable value for site works and improvements not included in other permits.

Non-Institutional Development

	Rate	Amount
For the first \$5,000 of contract value or part thereof	\$98.00	
For each \$1,000 of contract value or part thereof from \$5,001 to \$19,999	\$14.00	
For each \$1,000 of contract value or part thereof from \$20,000 to \$49,999	\$8.25	
For each \$1,000 of contract value or part thereof over \$50,000	\$7.00	
	Total	

Institutional Development

	Rate	Amount
For the first \$5,000 of contract value or part thereof	\$98.00	
For each \$1,000 of contract value or part thereof from \$5,001 to \$19,999	\$14.00	
For each \$1,000 of contract value or part thereof from \$20,000 to \$49,999	\$8.25	
For each \$1,000 of contract value or part thereof over \$50,000.00 to \$19,999,999	\$7.00	
For each \$1,000 of contract value or part thereof over \$20,000,000	\$3.80	
	Total	

Special Permit Services

For evaluation of plans, specifications, building materials, appliances, systems, equipment, methods of design and construction, pursuant to Clause 1.2.1.1.(1)(b), Division A of the 2012 BC Building Code:

For initial evaluation	\$225.00
For each hour or part thereof	\$113.00

For issuance of a partial permit in addition to the permit fee for the full project

For a partial permit	\$200.00
----------------------	----------

Other fees

For issuance of a permit for work which has already started	Double Permit Fee
To process a Permit Amendment, rate per hour or part thereof	\$113.00
Re-inspection due to faulty work or materials, rate per hour or part thereof	\$75.00
Special inspection during normal business hours, per hour or part thereof	\$75.00



THE UNIVERSITY OF BRITISH COLUMBIA
Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4

☎ 604.822.8228 • 📠 604.822.6119

DP # _____

Development Permit Application Form

Complete application form and prepare associated materials prior to scheduling an application intake meeting with the UBC Manager, Development Services.

Project Address and Building Name:
Description of Area:
Description of Project:

Applicant (authorized agent):		
Contact name:		
Mailing address:		Email:
City:	Postal Code:	Phone:
Architect:		
Contact name:		
Mailing address:		Email:
City:	Postal Code:	Phone:
Landscape Architect:		
Contact name:		
Mailing address:		Email:
City:	Postal Code:	Phone:

I, THE AUTHORIZED AGENT, GIVE CONSENT FOR CAMPUS & COMMUNITY PLANNING TO POST DIGITAL DRAWINGS AND SUPPORTING TEXT FOR PUBLIC VIEWING ON THEIR WEBSITE.

I HEREBY AGREE THAT I WILL COMPLY WITH ALL RULES, BYLAWS, REGULATIONS AND POLICIES OF THE UNIVERSITY OF BRITISH COLUMBIA AND ALL OTHER STATUTES, RULES, BYLAWS, POLICIES AND REGULATIONS OF OTHER AUTHORITIES IN FORCE AT THE UNIVERSITY OF BRITISH COLUMBIA RELATING TO THE WORK, UNDERTAKING OR PERMISSION IN RESPECT OF WHICH THIS APPLICATION IS MADE AND THAT I WILL INDEMNIFY AND SAVE HARMLESS THE UNIVERSITY OF BRITISH COLUMBIA, ITS OFFICIALS, EMPLOYEES AND AGENTS FROM ALL CLAIMS, LIABILITIES, JUDGEMENTS, COSTS OR EXPENSES OF EVERY KIND, INCLUDING NEGLIGENCE, IN RESPECT OF ANYTHING DONE OR NOT DONE IN CONSEQUENCE OF ANY PERMISSION, PERMIT OR LICENSE ISSUED AS A RESULT OF THE APPLICATION OR THE FAILURE TO OBSERVE COMPLETELY ALL STATUTES, RULES, BYLAWS, POLICIES AND REGULATIONS RELATING TO ANY WORK OR UNDERTAKING IN RESPECT OF WHICH THIS APPLICATION IS MADE.

SIGNED AT VANCOUVER, B.C. THIS _____ DAY OF _____ 20____

SIGNATURE OF AUTHORIZED AGENT: _____

Please continue application on reverse



DP Fee (see Fee Schedule below): All fees must be paid prior to the issuance of a permit.

Development permit projects		
Type of application: <input type="checkbox"/> Major (Value > \$2.5 Million) <input type="checkbox"/> Minor (Value < \$2.5 Million)	<input type="checkbox"/> New Building <input type="checkbox"/> Addition <input type="checkbox"/> Façade Alterations only	<input type="checkbox"/> Site / Park Design <input type="checkbox"/> Amendment <input type="checkbox"/> DP Extension
Gross Floor Area: <div style="text-align: center;">ft² or m²</div>	Permit fee:	Amount enclosed:
Payment by: <input type="checkbox"/> Cheque** <input type="checkbox"/> Cash <input type="checkbox"/> Work Order/Project#:		

Fee Schedule:

A	Minor Applications (Development Permit Board approval not required)	Fee
	For each 100 m ² up to 500 m ² GFA* (or part thereof)	\$350
	Additional GFA (rate per 100 m ² or part thereof)	\$150
	Maximum	\$15,000
B	Major Applications	Fee
	For each 100 m ² up to 500 m ² GFA* (or part thereof)	\$300
	Additional GFA (rate per 100 m ² or part thereof)	\$110
	Maximum	None
	REAP Applications - For Residential projects only, UBC REAP (Residential Environmental Assessment Program) certification is required. Documentation review and certification services provided by the Campus Sustainability Office (fee includes 5% GST).	\$3,150 (please provide a separate cheque)
C	Site Changes (includes Public Realm)	Fee
	Up to 1,000 m ² (rate per 200 m ² or part thereof)	\$250
	Additional area (rate per 200 m ² or part thereof)	\$85
	Maximum	\$5000
D	Alterations, Changes of Use	Fee
	For each 100 m ² GFA* (or part thereof)	\$290
	Maximum	\$2,350
E	Revisions	Fee
	Revisions to drawings resulting from non-compliance or insufficient information, or applicant's request	10% of fee that would apply to a new application (minimum fee \$160)
F	Minor Amendments	Fee
	Amendments where less than 15% of GFA or building exterior is altered or where less than 15% of GFA use is changed	25% of fee that would apply to a new application (minimum fee \$160)
G	Extensions and Renewals	Fee
	Extension of validity of development permit or renewal of a development permit which has become void	75% of fee that would apply to a new application (minimum fee \$340)

* GFA = gross floor area

** Submit separate cheques for each application and make payable to the 'University of British Columbia'

Note: Where public notice in community newspapers is required as part of the Development Permit process, Campus & Community Planning will coordinate the advertising, but the applicant is responsible for all costs.



DEVELOPMENT PERMIT APPLICATION CHECKLIST

Submission Requirements			Comments
Application Form	<ul style="list-style-type: none"> A Development Permit Application Form must be completed and signed at time of submission. 	<input type="checkbox"/>	
Application Fee	<ul style="list-style-type: none"> An application fee is due at time of submission. 	<input type="checkbox"/>	
Written Description	<ul style="list-style-type: none"> A description of the project, outlining the use, site context and rationale. 	<input type="checkbox"/>	
Design Policy Compliance	<ul style="list-style-type: none"> A brief written outline on how the project complies with the campus wide design guidelines (<i>Vancouver Campus Plan</i> Part 3) for academic projects or the design guidelines in the applicable neighbourhood plan for neighbourhood projects. 	<input type="checkbox"/>	
Title Search	<ul style="list-style-type: none"> Copy of current title search from the Land Title Office, for each parcel involved in the proposal (include Legal description and Property Identifier). 	<input type="checkbox"/>	
Site Profile	<ul style="list-style-type: none"> See <i>UBC Procedures Related to Contaminated Sites Regulation</i>. A Stage 1 Preliminary Site Investigation, Site Profile are required. http://riskmanagement.ubc.ca/environment/contaminated-site-procedures Environmental Compliance Check List is required http://planning.ubc.ca/sites/planning.ubc.ca/files/documents/planning-services/forms-documents/DP-Envtl-ComplianceChecklist-Jun13.pdf 	<input type="checkbox"/>	
Tree Survey	<ul style="list-style-type: none"> Location and identification of all existing trees and other significant plant material on-site. 	<input type="checkbox"/>	
Green Building Certification	<ul style="list-style-type: none"> Academic: Submit LEED checklist; min. LEED Gold and 42% below MNECB http://www.sustain.ubc.ca/campus-initiatives/buildings/leed-ubc Residential: Submit REAP checklist; min. REAP Gold http://sustain.ubc.ca/campus-initiatives/green-buildings/reap 	<input type="checkbox"/>	
Geotechnical Report	<ul style="list-style-type: none"> Prepared by a Geotechnical Engineer for potentially hazardous or unstable areas. 	<input type="checkbox"/>	
Photos	<ul style="list-style-type: none"> Pre-construction digital photos of site and surrounding context 	<input type="checkbox"/>	
DP Notification Sign	<ul style="list-style-type: none"> See Development Permit Notification Sign Guidelines below (photo verification required). 	<input type="checkbox"/>	
Building Signage	<ul style="list-style-type: none"> See <i>UBC Sign Standards and Guidelines</i> http://planning.ubc.ca/sites/planning.ubc.ca/files/attachments/2010_Sign_Guidelines.pdf 	<input type="checkbox"/>	
3D Model	<ul style="list-style-type: none"> 3D digital model of the project in Sketch-Up format. 	<input type="checkbox"/>	
Drawing Requirements One hardcopy set (11" x 17" and stapled only) and one digital set (email or CD of all drawings in PDF format).			
Cover Sheet with Project Statistics (Data Sheet)	<ul style="list-style-type: none"> Total Site Area and Site Coverage Net and Gross Floor Area by Use Building Height(s) Setbacks: Front Yard, Rear Yard and Side Yards (permitted + proposed) Number of Parking, loading and bicycle parking spaces (Class 1 + 2) (permitted + proposed) Number of Dwelling Units, unit sizes, bedrooms per unit + CRUs Floor Space Ratio permitted and proposed Summary of floor areas by level and exclusions (residential projects) List of variances requested and rationale 	<input type="checkbox"/>	
Context Plan	<ul style="list-style-type: none"> Plan showing the relationship of the proposed buildings to surrounding developments at front, rear and sides 	<input type="checkbox"/>	



THE UNIVERSITY OF BRITISH COLUMBIA

Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4

☎ 604.822.8228 • 📠 604.822.6119

Drawing Requirements (cont.)				Comments
Site Plan	<ul style="list-style-type: none"> • Address (if available) • Street name(s) • Dimensions of site • Location and dimensions of all buildings with north arrow • Required yards, setbacks and building lines • Size and location of all off street parking and loading 	<ul style="list-style-type: none"> • Access to parking and loading • Existing and finished grade levels • Treatment of open areas, courtyards, pedestrian areas, etc. • Location of garbage facilities • Location of fire hydrants and their distance from the subject site • Fire access routes or lanes • Area of proposed work if adding to an existing building (highlight) 	<input type="checkbox"/>	
Utilities	<ul style="list-style-type: none"> • Site Plan showing the adjacent existing utility lines, clearances between the building and existing utility lines and preliminary service connections to the existing utility systems (sign off by Utilities required prior to DP issuance) • Preliminary Service Connection Application Form to be submitted to Utilities. • <i>Residential projects only:</i> Submit a copy of the completed Energy Service Agreement with Corix Multi-Utility Services Inc. 		<input type="checkbox"/>	
Survey Plan	<ul style="list-style-type: none"> • Street address, street name(s) and location • Dimensions of site and site area, including north arrow • Location and dimensions of all existing buildings on the site • Ultimate property line • Lane dedications, registered easements, encroachments and right-of-ways must be indicated on the surveys • Location of existing street crossings • Existing grades at each of the four corners of the site • Existing grades at each corner of the existing and/or proposed principle building envelope 		<input type="checkbox"/>	
Shadow Analysis	<ul style="list-style-type: none"> • Spring / Summer at 10 am, 12 pm and 2 pm 		<input type="checkbox"/>	
Floor Plans	<ul style="list-style-type: none"> • All storeys including all levels of underground parking • All door, window and skylight locations • Location of vents, bay or box windows, air conditioning units and/or condensing units 		<input type="checkbox"/>	
Roof Plan	<ul style="list-style-type: none"> • Dimensions • Elevations of roof parapet, mechanical, elevator/stair housing, amenity areas 		<input type="checkbox"/>	
Elevations	<ul style="list-style-type: none"> • Elevation of front, rear, two sides and courtyard (if applicable) • Floor levels and height above and below finished grades • Exterior finishing details and materials • Elevation on each floor level, peak of pitched roof or parapet wall of flat roof • Door and window details and sizes • Weather protection • Accessory building details • Sign Location 		<input type="checkbox"/>	
Sections	<ul style="list-style-type: none"> • Longitudinal and cross sections • Details of vaulted areas and adjacent attic spaces • Envelope or height protrusions • Bay window, window seats and window well details 		<input type="checkbox"/>	
Landscape Plans	<ul style="list-style-type: none"> • Provide a full Landscape Plan illustrating both common and botanical names, sizes and quantity of all proposed plant material • Proposed plant material, paved surfaces and materials, other landscape elements and existing/proposed trees must be shown on Landscape Plan • Existing site contours, landscaping and material to be removed, include size, common name and location • All landscape elements and details, including new/existing surfaces to be retained, enclosures, site furniture, fences and structures 		<input type="checkbox"/>	
Lighting	<ul style="list-style-type: none"> • Proposed Lighting Plan is to comply with Lighting Guidelines (<i>Vancouver Campus Plan</i> Part 3 Sec. 2.5.2) 		<input type="checkbox"/>	



THE UNIVERSITY OF BRITISH COLUMBIA Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4
☎ 604.822.8228 • 📠 604.822.6119

DEVELOPMENT PERMIT NOTIFICATION SIGN GUIDELINES *

From UBC Development & Building Regulations, Section 1.10 Public Process: The applicant shall erect information signs in the specified format on or immediately adjacent to the site in location(s) approved by the Manager, Development Services for Development Permits. The sign must be in place no later than 1 week after submission of the application and shall remain until the project is complete or withdrawn, whichever comes first.

Size: The standard size is 4' x 8' (1.2 m x 2.4 m).

Lettering: The lettering is to be Helvetica and is to be black on a white background.

Construction Specifications: Standard format is a freestanding sign supported only by posts or poles where the top of the sign does not exceed 9 feet (2.75 m) in height above grade. All signs must be erected in a safe manner and be structurally sound to withstand wind and weather.

Location: Signs must be placed within the boundaries of the site, approximately but not closer than 6 feet (1.82 m) from any property line and such that it does not interfere with pedestrian or vehicular traffic. The sign must be located so that it can be clearly read from streets or lanes and be clear of all site obstructions. Where site is bounded by more than one street or corridor, more than one sign may be required.

Content: Signs must contain the information in the standard sign layout template below.

Prior to installation the applicant or agent must:

1. Submit a drawing of the proposed sign(s) and map indicating its (their) location to Campus & Community Planning (C&CP) for approval.
2. Advise in advance of the date of posting and call to confirm when the sign has been erected.

Following installation of all approved signs the applicant or agent must:

1. Submit dated photographs of all signage to C&CP.

Removal of Signs: The sign must be removed from the site at the applicant's cost 14 days after issuance of DP.

* **Note:** DP notification signs are not usually required for minor DP Applications; please check with C&CP.

Development Permit Sign Layout

↔ 8 ft ↔

NOTICE OF DEVELOPMENT PERMIT APPLICATION – No. DP XXXXX

(Name of the development)

(Applicant's name) have applied to the University of British Columbia for a Development Permit to construct (building type, storeys & units).
The total building area is _____ m².
Anticipated start of construction date

Public Open House

Date + Time:

Location:

Development Permit Board meeting details if applicable.

Developer's name:

Contact number:

For more information contact:

Karen Russell, Manager, Development Services

Campus & Community Planning

2210 West Mall, Vancouver, B.C. V6T 1Z4

Phone: (604) 822-1586, Fax: (604) 822-6119

Email: Karen.Russell@ubc.ca

<http://www.planning.ubc.ca>

Site Plan (24"x24")

Includes north arrow, street names, building names, lot dimensions & 'You are here'.

Site boundary in red, proposed building footprint in bold & crosshatched and existing building footprints



4 ft





SLP # _____

Streets and Landscape Permit Application Form

Complete application form and submit with all required materials to Campus and Community Planning.

Location (street address, legal address, cross streets, and/or place name):

Scope of Work (A description of the project, the rationale for the project, proposed changes and improvements):

Expected Start Date:

Expected Completion Date:

Type of Project:

☐ New SLP Project

☐ SLP Amendment

☐ SLP Extension

DP # (if applicable): _____

Applicant (authorized agent):

Contact name:

Mailing address:

Email:

City:

Postal Code:

Phone:

Contractor:

Contact name:

Mailing address:

Email:

City:

Postal Code:

Phone:

Other:

Contact name:

Mailing address:

Email:

City:

Postal Code:

Phone:

I HEREBY AGREE THAT I WILL COMPLY WITH ALL RULES, BYLAWS, REGULATIONS AND POLICIES OF THE UNIVERSITY OF BRITISH COLUMBIA AND ALL OTHER STATUTES, RULES, BYLAWS, POLICIES AND REGULATIONS OF OTHER AUTHORITIES IN FORCE AT THE UNIVERSITY OF BRITISH COLUMBIA RELATING TO THE WORK, UNDERTAKING OR PERMISSION IN RESPECT OF WHICH THIS APPLICATION IS MADE AND THAT I WILL INDEMNIFY AND SAVE HARMLESS THE UNIVERSITY OF BRITISH COLUMBIA, ITS OFFICIALS, EMPLOYEES AND AGENTS FROM ALL CLAIMS, LIABILITIES, JUDGEMENTS, COSTS OR EXPENSES OF EVERY KIND, INCLUDING NEGLIGENCE, IN RESPECT OF ANYTHING DONE OR NOT DONE IN CONSEQUENCE OF ANY PERMISSION, PERMIT OR LICENSE ISSUED AS A RESULT OF THE APPLICATION OR THE FAILURE TO OBSERVE COMPLETELY ALL STATUTES, RULES, BYLAWS, POLICIES AND REGULATIONS RELATING TO ANY WORK OR UNDERTAKING IN RESPECT OF WHICH THIS APPLICATION IS MADE.

SIGNED AT VANCOUVER, B.C. THIS _____ DAY OF _____ 20____

SIGNATURE OF AUTHORIZED AGENT: _____



SLP Fees and Deposits

Total Construction Value: \$ _____

(including all soft costs such as consultancy, project management etc.)

SLP Fee

Construction Value	%	Calculation
For the first portion up to \$250,000 (minimum \$250)	1.5%	
For the next portion from \$250,000 to \$500,000	1.00%	
For the next portion from \$500,001 to \$1,000,000	0.5%	
For the next portion from \$1,000,001 to \$2,000,000	0.25%	
For the next portion from \$2,000,001 to \$3,000,000	0.125%	
For the next portion over \$3,000,000	0.05%	
Total Fee:		\$ _____

SLP Amendment Fee	Calculation
10% of additional construction value (if applicable) or \$160	
Total Fee:	\$ _____

Non-refundable Damage Deposit Fee (\$200.00)*:

\$ _____

* For all UBC managed projects with a construction value under \$250,000 only.

Letter of Undertaking is required.

Refundable Damage Deposit

Construction Value	%	Calculation
For the first portion up to \$250,000	8%	
For the next portion from \$250,000 to \$500,000	4%	
For the next portion from \$500,001 to \$1,000,000	2%	
For the next portion over \$1,000,000	1%	
Total Damage Deposit:		\$ _____

Refundable Record Drawings Deposit

Record Drawings	
\$1,000 for each record drawing to be submitted upon project completion up to a maximum of \$20,000	_____ # of drawings
Total Record Drawings Deposit:	\$ _____

Total Fees and Deposits: \$ _____

Payment by: ☐ Cheque ☐ Cash ☐ Work Order / Project # _____



Streets and Landscape Permit Application Checklist

Submission Requirements			Comments
Application Form	• Streets and Landscape Permit Application Form (completed and signed)	<input type="checkbox"/>	
DP Issued	• Development Permit issued (if applicable) DP # _____	<input type="checkbox"/>	
Application Fee	• Due at time of submission (see SLP Fees and Deposits)	<input type="checkbox"/>	
Deposits	• Due at time of submission (see SLP Fees and Deposits)	<input type="checkbox"/>	
Drawings Required <ul style="list-style-type: none"> - One hardcopy set (11" x 17") and one digital set (all drawings in PDF format). - SLP Application submission documents must be at 95% completion. - Issued for Construction (IFC) drawings are required prior to the issuance of the Streets and Landscape Permit. 			
Photos	• Pre-construction digital photos of whole site and close-up photos of key features such as existing damaged infrastructure	<input type="checkbox"/>	
Survey Plan	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <ul style="list-style-type: none"> • Street address, street name(s) and location • Dimensions of site and site area, including north arrow • Location and building footprint dimensions of all existing buildings on the site. • Property line (if applicable) • Lane dedications, registered easements, encroachments and right-of-ways • Existing grades at each of the four corners of the site • Location of existing street crossings </div> <div style="width: 45%;"> <ul style="list-style-type: none"> • Road painting • Existing grades at each corner of existing and/or proposed building envelope • Benches • Signage • Banners & Fixtures • Planters • Bollards • Waste Bins • Bike Racks • Statues or commemorative plaques </div> </div>	<input type="checkbox"/>	
Context Plan	• Plan showing the relationship of the project area to surrounding streets and buildings in all directions	<input type="checkbox"/>	
Site Plan	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <ul style="list-style-type: none"> • Address • Street name(s) • Dimensions of site • Location of all building footprints • Size and location of all off-street parking and loading </div> <div style="width: 45%;"> <ul style="list-style-type: none"> • Surface treatment of open areas, courtyards, pedestrian areas, etc. • Location of garbage facilities • Location of fire hydrants closest to the subject site • Fire access routes or lanes </div> </div>	<input type="checkbox"/>	
Landscape Plan Drawings	<ul style="list-style-type: none"> • Identify and label common and botanical names, sizes and quantity of all proposed plant material/trees • Identify all landscape elements, plants and trees to be removed/relocated • All landscape elements, dimensions, and details, including new and existing surface materials, site furniture and structures 	<input type="checkbox"/>	
Material Samples	• Provide a sample of new surface material in proposed colour, unless specified in the UBC Technical Guidelines.	<input type="checkbox"/>	
Furniture Specifications	• Provide full specification for proposed street furniture, unless specified in the UBC Technical Guidelines.	<input type="checkbox"/>	
Proposed Site Grades and Drainage	• Provide all grading and drainage details on plan	<input type="checkbox"/>	
Civil Drawings	<ul style="list-style-type: none"> • Key Plan including Drawing Index and Legend • Road works including UBC typical cross sections • Geodetic datum, monument number, location, and elevation • Underground utilities (i.e. watermain, sanitary sewer, electrical, gas, etc.) <ul style="list-style-type: none"> ○ 1 drawing per utility • Staging/phases of work 	<input type="checkbox"/>	



THE UNIVERSITY OF BRITISH COLUMBIA

Campus and Community Planning

2210 West Mall • Vancouver, B.C. • V6T 1Z4

☎ 604.822.8228 • 📠 604.822.6119

Submission Requirements continued ...			Comments
Geotechnical Report	<ul style="list-style-type: none"> Prepared and signed by a Geotechnical Engineer identifying potentially hazardous or unstable areas 	<input type="checkbox"/>	
Stormwater Management and Erosion & Sediment Control Plans	<ul style="list-style-type: none"> Sediment and Erosion Control Methodology Truck access and egress routes Identify all measures taken to protect the environment – gravel access pad, cover existing catch basins, sediment check dam, wheel wash facility, etc. Weekly inspection of the system by record engineer and take samples during or after storm events with rainfall 10mm or greater Refer to UBC Technical Guidelines - http://www.technicalguidelines.ubc.ca 	<input type="checkbox"/>	
Hoarding Plan	<ul style="list-style-type: none"> Location of hoarding fences. (Note construction zone is to be minimized) 	<input type="checkbox"/>	
Construction Site Plan	<ul style="list-style-type: none"> Location of site office, first aid station, site entrances, storage and lay down locations, and tree protection fencing. The Hoarding Plan and Construction Plan may be combined 	<input type="checkbox"/>	
Traffic Management Plan	<ul style="list-style-type: none"> Truck routes to/from campus, street closures, traffic diversions, traffic control measures Emergency vehicle access route(s) Loading/Service locations Location of all excavations on streets or fire access routes. http://planning.ubc.ca/sites/planning.ubc.ca/files/documents/planning-services/forms-documents/TMP-ToR-ProjectInfoForm-Nov2011.pdf 	<input type="checkbox"/>	
Parking	<ul style="list-style-type: none"> List all construction vehicles including make, model, license plate number on site. Personal vehicles not permitted. 	<input type="checkbox"/>	
Site Profile	<ul style="list-style-type: none"> See <i>UBC Procedures Related to Contaminated Sites Regulation</i>. A Stage 1 Preliminary Site Investigation and Site Profile may be required. http://riskmanagement.ubc.ca/environment/contaminated-site-procedures Environmental Compliance Check List may be required http://planning.ubc.ca/sites/planning.ubc.ca/files/images/planning-services/forms-documents/DP-Envtl-ComplianceChecklist-Jun13.pdf 	<input type="checkbox"/>	
Tree Survey and/or Biophysical Assessment	<ul style="list-style-type: none"> Show location, size and identification of all existing trees and other significant plant material on-site. 	<input type="checkbox"/>	
Tree Protection Plan	<ul style="list-style-type: none"> A Tree Protection Plan shall be prepared and provided by the Landscape Architect and the Project Manager in accordance with the Vancouver Campus Plan Part 3 Section 2.4.6 - http://planning.ubc.ca/sites/planning.ubc.ca/files/documents/planning-services/policies-plans/VCP_Part3.pdf 	<input type="checkbox"/>	
Above and Below Ground Storage Tanks	<ul style="list-style-type: none"> Provide a plan identifying the type, size and location of all new or existing above or below ground storage tanks (including fuel tanks, acid neutralization tanks, oil water separators, grease traps, septic tanks, liquefied gas tanks, waste water collection and containment tanks), chillers and generators for acceptance by the Chief Risk Officer. 	<input type="checkbox"/>	



SLP Terms and Conditions

1. Streets and Landscape Permit (SLP) Valid Duration

The Streets and Landscape Permit (SLP) will expire after six (6) months from date of issue if project work has not commenced. It is the applicant's responsibility to re-apply to extend the expiry date of the SLP, at no additional charge, ten (10) working days prior to the expiration of the current permit.

2. Construction Fence

The construction site plan must clearly identify the location of the construction fence line.

3. Letter of Undertaking

For projects with a construction value of up to \$250,000, a non-refundable fee of \$200 and a Letter of Undertaking are required in lieu of a refundable damage deposit. The Project Manager (UBC Project Services or UBC Properties Trust) is required to submit a signed "**LETTER OF UNDERTAKING**" along with the full SLP application package. The Project Manager will be held responsible for deficiencies and damage in the landscape (hard and soft).

4. Refundable Damage Deposit

The applicant is to provide a Damage Deposit to be used to pay for any permanent or temporary repair and/or cleanup costs caused by construction activity. The Damage Deposit is to be submitted and payable to Campus and Community Planning (C&CP) in the form of a certified cheque or other acceptable form of credit. The applicant may apply for a refund of the Damage Deposit, with a formal written request (i.e. memo/letter), upon completion of all construction work and associated repair work. The refund request, to include a signed certification, must be received by C&CP from the coordinating Professional Engineer or Landscape Architect confirming that all capital improvement and restoration work has been completed in accordance with the SLP, that all required standards and codes have been adhered to, and that all damage to the surrounding areas has been restored. If the Damage Deposit is insufficient to cover all repair costs, the applicant will be billed for the balance. Repair work undertaken by the applicant must be approved by the University prior to commencement.

5. Street and Landscape Restoration

The applicant is responsible for restoring streets and landscape areas to the satisfaction of C&CP. Street restorations are to conform to the standards set in the City of Vancouver's Street Restoration Manual (http://vancouver.ca/files/cov/vancouver_street_restoration_manual.pdf). The University, prior to commencement, must approve any restoration work. If the digital photographs submitted as part of the application submission do not clearly illustrate the pre-construction condition of existing elements, C&CP will determine the level of restoration required.

6. Record Deposit Record Drawings

The applicant is to provide a Record Deposit based on the numbers of drawings submitted. The record drawings (signed and sealed by the Engineer of Record) must be submitted upon completion of the project. Similar to the Damage Deposit, the applicant may apply for a refund of the Record Deposit, with a formal written request, upon completion of all construction work and associated repair work. The record drawings are to be in the format approved in the Technical Guidelines.

7. Dissemination of Information and Adherence to the Building Permit Terms & Conditions

The applicant is responsible for ensuring all trades, contractors and subcontractors that work on the job site are aware of and comply with these Terms and Conditions as well as the standard Terms & Conditions for Building Permits - http://planning.ubc.ca/sites/planning.ubc.ca/files/documents/planning-services/forms-documents/BP-TermsConditions_Jan14.pdf

APPENDIX I

Risk Assessment

RISK REGISTER

Revision Issue Date: 2016-04-08

Project: NW Marine Dr.-East Mall-Chancellor Blvd. Intersection Redesign
Client: UBC Campus + Community Planning
Owners: Musqueam First Nation & BC Ministry of Transportation
Consultant: Van Augustine Consultants

Risk ID	Risk Allocation (Retained/Shared/Transferred)	Risk Category	Risk	Timing of Risk Event (Planning, Design, Construction, Operations)	Description	Consequence	Risk Treatment (Avoid, Transfer, Mitigate, Accept)
1	Retained by Client	Site	Risk of protracted encroachment negotiations prior to roundabout construction	Design	Risk that Metro Vancouver might not accommodate encroachment upon the Pacific Spirit Park property line	Delay in select project works related to roundabout construction due to negotiations	Mitigate: Ministry of Transportation and Infrastructure is experienced in property negotiations with the regional body and can ensure timely grant of easement
2	Retained by Client	Planning	Risk of lengthy utility crossing permit approval periods prior to commencing utility/road works	Construction	Risk that utility owner approval process for the proposed works is longer than anticipated	Delay in roadworks construction commencement and completion, resulting in increased cost and traffic disruption during the start of school year due to the overlap between construction and academic schedules	Mitigate: UBC Campus + Community Planning can ensure that approval time is conservative in project planning timelines and ensure sound procedures are carried out
3	Transferred to Client	Design/Site	Risk of overestimation of catchment area for the stormwater system	Design	Risk that size of catchment area estimated to be draining into the site is overly conservative	Excessive expenditure associated with the oversized components of the stormwater management system	Mitigate: UBC Campus + Community Planning to supply reliable topographical information
4	Transferred to Contractor	Construction	Risk of existing invert elevations or manhole depths not being able to support the proposed system	Construction	Design of the new minor system assumes that the proposed upgrades can be accommodated around the existing infrastructure, and that the existing manhole barrel depths and mainline inverts will accommodate the bypass system that directs water to the underground detention facility	If invert elevations or manhole depths are not able to support the proposed system, an alternative configuration will need to be designed	Mitigate: Sequencing the roadworks after the completion of the Bike Garden helps mitigate this risk as the month of May is available for detailed utility survey and any necessary design revisions.


5	Shared with Client	Site	Risk of lengthy approval process associated with the construction plans for the Bike Park Gateway Building	Design	Risk that client review of gateway building plans is more drawn out than expected	Delay in building construction, completion and service commissioning. Trucks bringing in construction materials and taking out any excavated materials may cause traffic disruption during the high-traffic time the school year	Mitigate: UBC Campus + Community Planning has proposed an on-going review process to identify deficiencies in the building plans as early as possible
6	Transferred to Contractor	Construction	Risk that traffic volumes higher than those anticipated are experienced during the construction phase.	Construction	Traffic volumes higher than those anticipated are experienced during construction	May require the enforcement of additional traffic management measures. Also, increased traffic may slow down roadwork and construction activities, resulting in an off-schedule delivery	Mitigate: Inflation of traffic mangement budget.

APPENDIX J

Stakeholder Engagement Strategy

Stakeholder Engagement Framework

Different stakeholder group require different levels of engagement at different stages in the project. To maintain consistency and transparency the following consultation model is followed once an engagement activity has been selected.



(Adapted from WDO, 2013)

Stakeholder Registry

Project: NW Marine Dr./ Chancellor Blvd./ East Mall Intersection Redesign

Client: UBC Campus and Community Planning

Highest: 5 Lowest: 1		Power	Level of Concern	Location	Position	Expectations and Roles of stakeholders
		(Direct Control, Influence)	(Interest, Technical, Non-technical)	Internal/ External	Support/ Neutral/ Resist	
Stakeholder Name/ Group		Score: 1-5	Score: 1-5	Score: I / E	Score: S / N / R	
1	UBC Board of Governors	5	3	I	S or N	Funder/Decision Maker
2	UBC Senate	5	3	I	S or N	Funder/Decision Maker
3	UBC Campus and Community Planning	5	5	I	S	Coordinator
4	UBC Students	1	2	I	N	User
5	Alma Masters Society	3	2	I	S	User/ Indirect Financial Contributor
6	UBC Transportation Committee	3	4	I	S	Decision Maker
7	UBC Building Operations	2	1	I	N	Site Neighbor
8	UBC Facilities Management	2	1	I	N	Site Neighbor
9	Chan Centre	2	3	I	N or R	Site Neighbor / Destination for Users
10	Museum of Anthropology	2	3	I	N or R	Destination for Users
11	Musqueam First Nation	1	1	E	N	Owner
12	BC MOTI	5	5	E	S	Owner/Maintainer/ Regulator
13	Metro Vancouver	4	3	E	N or R	Decision Maker (to be confirmed)
14	Translink	3	4	E	N or R	User
15	Utility Owners	1	3	E	N or R	Service Provider
16	UBC Community Members	1	2	E	S and R	User
17	Nearby Residents	1	5	E	S and R	User / Site Neighbor
18	UBC Faculty Association	4	1	E	N	User
19	University Neighborhoods Association	3	3	E	S	User
20	UBC Community Liaison Committee	3	3	E	S	User
21	UEL Administration	3	3	E	S an R	User
22	UEL Citizens Advisory Committee	3	3	E	S and R	User
23	General Public	2	2	E	N	User




Figure 25: Stakeholder Classification